

MARINE NAVIGATION SIGNAL LIGHT

Daylight Signal Light/Charger CXD8,CXD8-CDX

Used to daylight signal communication between ships

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Navigation Signal Light
Standard	EN
Weight / Size	Dia9.5 Weight:2.6kgs CXD8-CDX Charger Input:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Navigation Signal Light	Model / SKU	Daylight-Signal-Light-Charger-CXD8-CXD8-CDX
Standard	EN	Weight / Size	Dia9.5 Weight:2.6kgs CXD8-CDX Charger Input:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- China Daylight Signal Light/Charger CXD8,CXD8-CDX:
- Main Introduction:

China Daylight Signal Light/Charger CXD8,CXD8-CDX:

Used to daylight signal communication between ships

Main Introduction:

1. Aluminum shell and Mechanical flash device.



2. Light Convenient to operate.

CXD8 Daylight Signal Light
Voltage: 24V
Power:60W
Light Pillar Angle:6°
Light Intensity:60000cd
Telescope Magnification:4
Telescope Visual Angle:3°
Visibility:2n.m
Lamp Holder:G6.35
Plug:25M-4A Four Pin
Protection Class:IP44
Cable Diameter: Dia9.5
Weight:2.6kgs
CXD8-CDX Charger
Input: AC110V/60Hz, AC-220V/50Hz/60Hz
Output: AC24V,AC12V/DC24V.DC12V
Capacity:7Ah
Temperature:-25-45 Ceisus Dgree
Socket: 25-4B, 25-3B
Protection Class:IP56
Weight:3.6KGS

4 pin socket for CXD8 Light



