MARINE NAVIGATION SIGNAL LIGHT

# Daylight Signal Light/Charger CXD8,CXD8-CDX

Used to daylight signal communicaiton between ships

ISO9001 Supplier

Class Certificate

Export Supply




## Key Highlights

| | |
|---|---|
| **Category** | Marine Navigation Signal Light |
| **Standard** | EN |
| **Weight / Size** | Dia9.5 Weight:2.6kgs CXD8-CDX Charger Input: |
| **Certificate** | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

## Technical Specifications

| | | | |
|---|---|---|---|
| **Category** | Marine Navigation Signal Light | **Model / SKU** | Daylight-Signal-Light-Charger-CXD8-CXD8-CDX |
| **Standard** | EN | **Weight / Size** | Dia9.5 Weight:2.6kgs CXD8-CDX Charger Input: |
| **Certificate** | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS | **Warranty** | 12 Months unless specified otherwise |
| **Origin** | China | | |

**CONTENTS**

- China Daylight Signal Light/Charger CXD8,CXD8-CDX:
- Main Introduction:

## China Daylight Signal Light/Charger CXD8,CXD8-CDX:

Used to daylight signal communicaiton between ships

## Main Introduction:

1. Aluminum shell and Mechanical flash device.

2. Light Convenient to operate.

| CXD8 Daylight Signal Light |
| --- |
| Voltage: 24V |
| Power:60W |
| Light Pillar Angle:6$^{o}$ |
| Light Intensity:60000cd |
| Telescope Magnification:4 |
| Telescope Visual Angle:3$^{o}$ |
| Visibility:2n.m |
| Lamp Holder:G6.35 |
| Plug:25M-4A Four Pin |
| Protection Class:IP44 |
| Cable Diameter: Dia9.5 |
| Weight:2.6kgs |
| CXD8-CDX Charger |
| Input: AC110V/60Hz, AC-220V/50Hz/60Hz |
| Output: AC24V,AC12V/DC24V.DC12V |
| Capacity:7Ah |
| Temperature:-25-45 Ceisus Dgree |
| Socket: 25-4B, 25-3B |
| Protection Class:IP56 |
| Weight:3.6KGS |

4 pin socket for CXD8 Light




jinbomarine.com


jinbomarine.com