

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

## OTHER MARINE VALVES & ACCESSORIES

# Deck Scupper Type SB/SBS/SC/SCS CB/T3885-2004

ISO9001 Supplier

Class Certificate

Export Supply

Deck Scupper Standard: CB/T 3885-2004 It should pass the sealing test which lasts for 5 minutes under the 0.12Mpa water pressure. Type: Type Descriptions ...



### Key Highlights

<b>Category</b>	Other Marine Valves & Accessories
<b>Standard</b>	GB
<b>Material</b>	Carbon Steel with Galvanization
<b>Weight / Size</b>	Type Descriptions Nominal Size(mm) YA Round Deck Scupper 32~80 YB Round ...
<b>Certificate</b>	Mill certificate

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
<b>Category</b>	Other Marine Valves & Accessories	<b>Model / SKU</b>	Deck-Scupper-Type-SB-SBS-SC-SCS-CB-T3885-2004
<b>Standard</b>	GB	<b>Material</b>	Carbon Steel with Galvanization
<b>Weight / Size</b>	Type Descriptions Nominal Size(mm) YA Round Deck Scupper 32~80 YB Round Deck Scupper with flange, flange size as per GB/T10751-1989 32~40 YBS Round Deck Scupper with flange, flange size as per GB/T2506-1989 32~65 YC Flat Round Deck Scupper 32~100 YD Short-tube Round Deck Scupper 40~65 TA Oval Deck Scupper 80~150 TB Oval Deck Scupper with flange, flange size as per CB/T46-1999 TBS Oval Deck Scupper with flange, flange size as per GB/T2506-1989 SA Water Sealed Deck Scupper with Flange, flange size as per CB/T46-1999 & GB/T10751-1989 40~100 SAS Water Sealed Deck Scupper with Flange, flange size as per GB/T2506-1989 50~100 SB Bolted Water Sealed Deck Scupper with Flange, flange size as per CB/T46-1999 & GB/T10751-1989 40~100 SBS Bolted Water Sealed Deck Scupper with Falnge, flange size as per GB/T2506-1989 50~100 SC Welded Water Sealed Deck Scupper with Falnge, flange size as per CB/T46-1999 & GB/T10751-1989 40~100 SCS Welded Water Sealed Deck Scupper with Falnge, flange size as per GB/T2506-1989 50~100 Main Parts & Size:	<b>Certificate</b>	Mill certificate
<b>Warranty</b>	12 Months unless specified otherwise	<b>Origin</b>	China



SCS	Welded Water Sealed Deck Scupper with Falnge, flange siz as per GB/T2506-1989	50~100
-----	---	--------

## Main Parts & Size:

Body---Carbon Steel with Galv

Grill---Carbon Steel with Galv

Water Seal Cover---Carbon Steel with Galv

Stem---Aluminum Bronze

Screw---Brass

## Main Size List for SB (mm):

DN	Dw	D0	D2	D3	D4	H	H1	$\delta \leq$	t1	t2	Flange Size						b	d0	Weight(kgs)
											As per GB/T10751-1989			As per CB/T46-1999					
											A	B	D1	D	D1	n			
40	48	137	133	170	220	200	135	100	5	3	132	95	100	—	—	—	16	14	6.1
50	60					210	146		6	4	—	—	—	135	103	6	14	15	9.39
65	76	163	159	195	225	220	156		6.5	4.5				155	123				12.94
80	89	184	180	215	240	260	197	150	7					170	138				17.11
100	114	207	203	230	260	265	208		8	5				190	158	8			19.39

## Main Size List for SBS (mm):

DN	Dw	D0	D2	H	H1	$\delta \leq$	t1	t2	Flange Size					weight(kgs)
									As per GB/T 2506-1989					
									D	D1	b	d0	n	
50	60	118	114	120	75	60	6	4	140	110	16	14	4	5.8
65	76	144	140		80		6.5	4.5	160	130				7.4
80	89	172	168	170	15	110	7		190	150	18			9.3
100	114	207	203		125		8	5	210	170				12.5

## Main Size List for SC (mm):

DN	Dw	D0	D2	H	H1	$\delta \leq$	t1	t2	Flange Size						b	d0	Weight(kgs)
									As per GB/T10751-1989			As per CB/T46-1999					
									A	B	D1	D	D1	n			
40	48	137	133	200	135	100	5	3	132	95	100	—	—	—	16	14	5.17
50	60			210	146		6	4	—	—	—	135	103	6	14	15	5.93
65	76	163	159	220	156		6.5	4.5				155	123				8.27
80	89	184	180	260	197	150	7					170	138				12.69
100	114	207	203	265	208		8	5				190	158	8			14.99

## Main Size List for SCS (mm):

DN	Dw	D0	D2	Normal			Extended			t1	t2	Flange Size					weight(kgs)	
				H	H1	$\delta \leq$	H	H1	$\delta \leq$			As per GB/T 2506-1989					Normal	Extended
												D	D1	b	d0	n		
50	60	137	133	210	146	100	260	196	150	6	4	140	110	16	14	4	6.9	7.2
65	76	163	159	220	156		270	206		6.5	4.5	160	130				9.8	10.2
80	89	184	180	260	197		310	247	200	7	190	150	18		14		14.5	
100	114	207	203	265	208		315	258		8	5	210			170		16.6	17.4