

## CONNECTORS

# Detachable Chain Connecting Link C type

ISO9001 Supplier

Class Certificate

Export Supply

Connecting Link C type is used for connecting the mooring lines for the same size, widely used for mooring chains. Main Specification: CHAIN SIZE A B ...



## Key Highlights

<b>Category</b>	Connectors
<b>Material</b>	20MN2
<b>Weight / Size</b>	Connecting Link C type is used for connecting the mooring lines for the ...
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

## Technical Specifications

<b>Category</b>	Connectors	<b>Model / SKU</b>	Detachable-Chain-Connecting-Link-C-type
<b>Material</b>	20MN2	<b>Weight / Size</b>	Connecting Link C type is used for connecting the mooring lines for the same size, widely used for mooring chains.
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	<b>Warranty</b>	12 Months unless specified otherwise
<b>Origin</b>	China		

## CONTENTS

- China Detachable Chain Connecting Link C type:

- Main Specification:

## China Detachable Chain Connecting Link C type:



Connecting Link C type is used for connecting the mooring lines for the same size, widely used for mooring chains.

### Main Specification:

CHAIN SIZE		A	B	C	D	E	F	G	WEIGHT		PROOF TEST	BREAK TEST
m	inch	mm	mm	mm	mm	mm	mm	mm	kg	lbs	KGF	KGF
13-16	1/2 - 5/8	95	63	22	16	19	21	12	0.5	1	14651	23668
19	3/4	114	74	24	19	22	24	13	1	2	21771	34020
21-22	13/16 - 7/8	133	86	28	22	25	28	16	1.5	3.5	29030	44452
24-25	15/16 - 1	152	102	35	25	29	31	17	2.3	5.1	38000	54300
27-29	1 - 1/16 - 1 - 1/8	172	114	40	29	32	35	19	3.3	7.3	49200	70400
30-32	1 - 3/16 - 1 - 1/4	191	127	44	32	36	39	21	4.6	10.1	59500	84900
33-35	1 - 5/16 - 1 - 3/8	210	140	48	35	40	43	23	6.2	13.7	70700	101300
36-38	1 - 7/16 - 1 - 1/2	229	152	53	38	43	47	26	7.9	17.4	83300	118900

40-42	1-9/16 - 1-5/8	248	165	57	42	47	50	28	10	2 2	102000	143400
43-44	1-11/16 - 1-3/4	267	178	62	45	50	56	30	12 .5	2 7. 6	111900	159900
46-48	1-13/16 - 1-7/8	286	191	64	48	55	60	32	14 .5	3 2	130000	185100
50-51	1-15/16 - 2	305	197	64	51	59	64	34	16 .3	3 5. 9	145400	207700
52-54	2-1/16 - 2-1/8	324	209	67	54	63	68	36	20	4 4. 1	162000	231500
56-58	2-3/16 - 2-1/4	343	222	71	58	66	71	38	23 .6	5 2	185400	265000
59-60	2-5/16 - 2-3/8	364	235	78	61	70	76	41	28	6 1. 7	199600	285200
62-64	2-7/16 - 2-1/2	381	246	79	64	74	79	43	32 .2	7 1	223000	319000
66-67	2-9/16 - 2-5/8	400	259	83	67	77	83	45	37	8 1. 6	242900	347000
68-70	2-11/16 - 2-3/4	419	271	87	70	81	87	47	45	9 9. 2	263500	376400
71-73	2-13/16 - 2-7/8	438	283	91	73	85	91	49	49	1 0 8	285000	407000
75-76	2-15/16 - 3	457	296	95	76	88	95	51	55	1 2 1	308200	440200

78-79	3-1/16 - 3-1/8	476	308	99	79	92	99	53	63	1 3 9	332100	474500
81-83	3-3/16 - 3-1/4	495	320	103	83	96	103	55	73	1 6 1	360400	514800
84-86	3-5/16 - 3-3/8	514	333	107	86	99	107	57	80	1 7 6	384400	549100
87-89	3-7/16 - 3-1/2	533	345	111	89	103	111	60	93	2 0 5	409000	584300
90-92	3-9/16 - 3-5/8	553	357	115	92	107	115	62	97	2 1 5	434800	621200
94-95	3-11/16 - 3-3/4	572	370	119	95	111	119	64	116 2	2 5 6	462300	660100
97-98	3-13/16 - 3-7/8	591	382	128	98	114	123	66	123	2 7 1	490000	700000
100-102	3-15/16 - 4	610	394	132	102	118	127	68	131	2 8 9	522100	746000
105	4-1/8	629	419	147	105	127	132	70	175	3 8 6	550000	785000
111	4-3/8	667	456	167	111	138	140	75	208	4 5 9	607000	867200
114	4-1/2	686	480	190	114	147	144	77	227	5 0 0	637300	910900

For more information, please feel free to contact us.