CONNECTORS

Detachable Chain Connecting Link C type

ISO9001 Supplier

Class Certificate

Export Supply

Connecting Link C type is used for connecting the mooring lines for the same size, widely used for mooring chains. Main Specification: CHAIN SIZE A B ...



Key Highlights

Category	Connectors
Material	20MN2
Weight / Size	Connecting Link C type is used for connecting the mooring lines for the ...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Connectors	**Model / SKU**	Detachable-Chain-Connecting-Link-C-type
Material	20MN2	**Weight / Size**	Connecting Link C type is used for connecting the mooring lines for the same size, widely used for mooring chains.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS

- China Detachable Chain Connecting Link C type:
- Main Specification:

China Detachable Chain Connecting Link C type:



Connecting Link C type is used for connecting the mooring lines for the same size, widely used for mooring chains.

Main Specification:

CHAIN SIZE		A	B	C	D	E	F	G	WEIGHT		PROOF TEST	BREAK TEST
mm	inches	mm	mm	mm	mm	mm	mm	mm	kg	lbs	KGF	KGF
13-16	1/2 - 5/8	95	63	22	16	19	21	12	0.5	1	14651	23668
19	3/4	114	74	24	19	22	24	13	1	2	21771	34020
21-22	13/16 - 7/8	133	86	28	22	25	28	16	1.5	3.5	29030	44452
24-25	15/16 - 1	152	102	35	25	29	31	17	2.3	5.1	38000	54300
27-29	1-1/16 - 1-1/8	172	114	40	29	32	35	19	3.3	7.3	49200	70400
30-32	1-3/16 - 1-1/4	191	127	44	32	36	39	21	4.6	10.1	59500	84900
33-35	1-5/16 - 1-3/8	210	140	48	35	40	43	23	6.2	13.7	70700	101300
36-38	1-7/16 - 1-1/2	229	152	53	38	43	47	26	7.9	17.4	83300	118900

40-42	1-9/16 - 1-5/8	248	165	57	42	47	50	28	10	22	102000	143400
43-44	1-11/16 - 1-3/4	267	178	62	45	50	56	30	12.5	27.6	111900	159900
46-48	1-13/16 - 1-7/8	286	191	64	48	55	60	32	14.5	32	130000	185100
50-51	1-15/16 - 2	305	197	64	51	59	64	34	16.3	35.9	145400	207700
52-54	2-1/16 - 2-1/8	324	209	67	54	63	68	36	20	44.1	162000	231500
56-58	2-3/16 - 2-1/4	343	222	71	58	66	71	38	23.6	52	185400	265000
59-60	2-5/16 - 2-3/8	364	235	78	61	70	76	41	28	61.7	199600	285200
62-64	2-7/16 - 2-1/2	381	246	79	64	74	79	43	32.2	71	223000	319000
66-67	2-9/16 - 2-5/8	400	259	83	67	77	83	45	37	81.6	242900	347000
68-70	2-11/16 - 2-3/4	419	271	87	70	81	87	47	45	99.2	263500	376400
71-73	2-13/16 - 2-7/8	438	283	91	73	85	91	49	49	108	285000	407000
75-76	2-15/16 - 3	457	296	95	76	88	95	51	55	121	308200	440200

78-79	3-1/16 - 3-1/8	476	308	99	79	92	99	53	63	139	332100	474500
81-83	3-3/16 - 3-1/4	495	320	103	83	96	103	55	73	161	360400	514800
84-86	3-5/16 - 3-3/8	514	333	107	86	99	107	57	80	176	384400	549100
87-89	3-7/16 - 3-1/2	533	345	111	89	103	111	60	93	205	409000	584300
90-92	3-9/16 - 3-5/8	553	357	115	92	107	115	62	97.6	215	434800	621200
94-95	3-11/16 - 3-3/4	572	370	119	95	111	119	64	116.2	256	462300	660100
97-98	3-13/16 - 3-7/8	591	382	128	98	114	123	66	123	271	490000	700000
100-102	3-15/16 - 4	610	394	132	102	118	127	68	131	289	522100	746000
105	4 1/8	629	419	147	105	127	132	70	175	386	550000	785000
111	4 3/8	667	456	167	111	138	140	75	208	459	607000	867200
114	4 1/2	686	480	190	114	147	144	77	227	500	637300	910900

For more information, please feel free to contact us.