

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

DIESEL ENGINE DRIVEN WATER PUMP

Diesel self-priming water pump

Diesel self-priming water pump Parameter Diesel self-priming water pump Set Model 50KB-2D 80KB-3D ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Diesel engine driven water pump
Standard	EN
Weight / Size	Head lift(m) 30 30 25 Max.Suction head(m) 8 8 8 Engine Engine model 170F...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
Category	Diesel engine driven water pump	Model / SKU	Diesel-self-priming-water-pump
Standard	EN	Weight / Size	Head lift(m) 30 30 25 Max.Suction head(m) 8 8 8 Engine Engine model 170F 178F 186F Engine type Single cylinder,4-stroke,air cooled diesel engine Displacement(CC) 211 296 418 Max.output power(HP) 5 7 10 Rated spee(RPM) 3600 3600 3600 Fuel consumption ratio(g/kw.h) <284 <286 <280 starting method Recoil start Fuel tank capacity(L) 2.65 3.3 5.5 Options Electric starter N/A Available Available Oil annunciator N/A Available Available Pack Packing size(mm) 500x425x505 575x460x575 670x500x625 Net weight(Kgs) 34 45 66 Gross weight(Kgs) 36 49 70 20FT Qty 236 196 112
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	■ Diesel self-priming water pump	■ Parameter
----------	----------------------------------	-------------

Diesel self-priming water pump

Parameter

Diesel self-priming water pump				
Set	Model	50KB-2D	80KB-3D	100KB-4D
	Name	Diesel self-priming water pump		
	Inlet/Outlet diameter	50mm(2")	80mm(3")	100mm(4")
	Cont. Capacity(m3/h)	33	60	80
	Cont. Head lift(m)	30	30	25
	Max.Suction head(m)	8	8	8



Engine	Engine model	170F	178F	186F
	Engine type	Single cylinder,4-stroke,air cooled diesel engine		
	Displacement(CC)	211	296	418
	Max.output power(HP)	5	7	10
	Rated spee(RPM)	3600	3600	3600
	Fuel consumption ratio(g/kw.h)	<284	<286	<280
	starting method	Recoil start		
	Fuel tank capacity(L)	2.65	3.3	5.5
Options	Electric starter	N/A	Available	Available
	Oil annunciator	N/A	Available	Available
Pack	Packing size(mm)	500x425x505	575x460x575	670x500x625
	Net weight(Kgs)	34	45	66
	Gross weight(Kgs)	36	49	70
	20FT Qty	236	196	112