OIL SPILL DISPOSE DEVICE

Disc Oil Skimmer

ISO9001 Supplier

Class Certificate

Export Supply

Disc oil skimmer Disc oil skimmer is a portable, efficient oil spill recovery unit, consisting of floating skimmer above water, power system on shore or vessel and pipelines connecting them. It is applicable in ...



Key Highlights

Category	Oil Spill Dispose Device
Standard	EN
Weight / Size	Light weight, easy transference, applicable in oil spill emergency respo...
Certificate	ISO9001-2000

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Oil Spill Dispose Device	**Model / SKU**	Disc-Oil-Skimmer
Standard	EN	**Weight / Size**	Light weight, easy transference, applicable in oil spill emergency response.
Certificate	ISO9001-2000	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS

- Disc oil skimmer
- Technical parameter
- Features:

Disc oil skimmer

Disc oil skimmer is a portable, efficient oil spill recovery unit, consisting of floating skimmer above water, power system on shore or vessel and pipelines connecting them. It is applicable in pools, lakes, rivers and ocean.

Features:

- High efficiency
- Capability of reclaiming oil, crude oil, vegetable oil and other fluid oil
- Low water capacity in reclaimed oil
- Low draft, good buoyancy in waves.
- Light weight, easy transference, applicable in oil spill emergency response.

Technical parameter

Skimmer mode			ZSY5	ZS15	ZSY20	ZS30	ZS60
Maximum oil reclaim rate			5	15	20	30	8
Oil skimmer	Mass (kg)		42	76	110	170	710
	External dimension (mm)	Length	920	1100	1500	1650	2400
		Width	750	1100	1100	1650	2400
		Height	400	550	600	700	1750
	Draft (mm)		110-150	240-280	280-310	380-420	630-660
Power station	Power(kw)		4/3	6.6/5.5	6.6/5.5	28	35
	Mass (kg)		180/215	190/215	190/245	800	980
	Overall dimensions (mm)	Length	1050/1050	1050/1050	1050/1050	2000	1800
		Width	700/780	700/780	700/780	1050	1000
		Height	830/950	830/950	830/950	1200	1350
	Maximum delivery lift		12m	12m	12m	20m	30m
	Maximum suction lift		4.5m	4.5m	4.5m	5m	5m