HIGH PRESSURE PUMP

Double Acting Hollow Jack

Double Acting Hollow Jack   Product features: Double acting design, hydraulic reset. Hollow plunger design can be used for both pull and push. Equipped with safety valve to prevent damage caused by overpressure...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	High Pressure Pump
Standard	EN
Weight / Size	Model TCapacity mm Stroke mm Height mmMax Height mmDiameter mmDi...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	High Pressure Pump	**Model / SKU**	Double-Acting-Hollow-Jack
Standard	EN	**Weight / Size**	Model TCapacity mm Stroke mm Height mmMax Height mmDiameter mmDiameter cm²Area kgWeight RRH-307 30 178 330 508 114 33.3 47.68 22 RRH - 3010 30 257 432 689 114 33.3 47.68 27 RRH - 603 60 89 248 337 159 53.8 88.5 28 RRH-606 60 165 324 489 159 53.8 88.5 35 RRH-6010 60 257 438 695 159 53.8 88.5 46 RRH-1001 100 38 165 203 213 79.2 148.36 39 RRH-1003 100 76 254 330 213 79.2 148.36 61 RRH-1006 100 152 342 495 213 79.2 148.36 79 RRH-10010 100 257 460 718 213 79.2 148.36 107 RRH-1508 150 203 349 552 248 79.5 148.36 111
Surface	Painted	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

China Double Acting Hollow Jack:

Double Acting Hollow Jack

Product features:

Double acting design, hydraulic reset.

Hollow plunger design can be used for both pull and push.

Equipped with safety valve to prevent damage caused by overpressure.

Painted surface for greater corrosion resistance.

All models include quick connectors and dust caps.

Equipped with a dust ring to reduce pollution and prolong the life of the jack.

Model	T Capacity	mm Stroke	mm Height	mm Max Height	mm Diameter	mm Diameter	cm² Area	kg Weight
RRH-307	30	178	330	508	114	33.3	47.68	22
RRH - 3010	30	257	432	689	114	33.3	47.68	27
RRH - 603	60	89	248	337	159	53.8	88.5	28

RRH-606	60	165	324	489	159	53.8	88.5	35
RRH-6010	60	257	438	695	159	53.8	88.5	46
RRH-1001	100	38	165	203	213	79.2	148.36	39
RRH-1003	100	76	254	330	213	79.2	148.36	61
RRH-1006	100	152	342	495	213	79.2	148.36	79
RRH-10010	100	257	460	718	213	79.2	148.36	107
RRH-1508	150	203	349	552	248	79.5	148.36	111