

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

## MARINE NAVIGATION SIGNAL LIGHT

# Double Deck Navigation Signal Light CXH-101P

ISO9001 Supplier

Class Certificate

Export Supply

The Navigation Signal Light used to the ship with length 50M or above as lamp signal liaison when night navigation.



### Key Highlights

<b>Category</b>	Marine Navigation Signal Light
<b>Standard</b>	ISO
<b>Material</b>	Engineering Plastic, Steel, Stainless Steel
<b>Weight / Size</b>	Voltage 24V 110V 220V Power 2X60W 2X65W 2X65W Lamp Holder B22d Protectio...
<b>Certificate</b>	CCS Type Approval Certificate

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Navigation Signal Light	Model / SKU	Double-Deck-Navigation-Signal-Light-CXH-101P
Standard	ISO	Material	Engineering Plastic, Steel, Stainless Steel
Weight / Size	Voltage 24V 110V 220V Power 2X60W 2X65W 2X65W Lamp Holder B22d Protection Class IP56 Cable Outside Diameter Dia.12-13 Name Type Visibility Level Arc Color Weight Starboard Light CXH1-10P 3n.m 112.5o Green 3.8KGS Port Light CXH2-10P 3n.m 112.5o Red 3.8KGS Masthead Light CXH3-10P 3n.m 225o White 3.7KGS Stern Light CXH4-10P 3n.m 135o White/Yellow 3.7KGS All-round-Light CXH6-10P 3n.m 360o Red/green/white 3.6KGS	Certificate	CCS Type Approval Certificate
Warranty	12 Months unless specified otherwise	Origin	China

<b>CONTENTS</b>	■ China Double Deck Navigation Signal Light CXH-101P:	■ Standards:
	■ Main Specification:	

## China Double Deck Navigation Signal Light CXH-101P:



The Navigation Signal Light used to the ship with length 50M or above as lamp signal liaison when night navigation.

### Standards:

1. Confirm to the international regulation for preventing collision at sea, 1972 and grade entry norms for navigation lights



2. Confirm to the International Standard IEC60598-1-2008.
3. Confirm to the standard of marine electric signal light's technical condition GB/T 3028-2012.

## Main Specification:

Voltage	24V	110V	220V
Power	2X60W	2X65W	2X65W
Lamp Holder	B22d		
Protection Class	IP56		
Cable Outside Diameter	Dia.12-13		

Name	Type	Visibility	Level Arc	Color	Weight
Starboard Light	CXH1-10P	3n.m	112.5°	Green	3.8KGS
Port Light	CXH2-10P	3n.m	112.5°	Red	3.8KGS
Masthead Light	CXH3-10P	3n.m	225°	White	3.7KGS
Stern Light	CXH4-10P	3n.m	135°	White/Yellow	3.7KGS
All-round- Light	CXH6-10P	3n.m	360°	Red/green/white	3.6KGS

