

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

MARINE NAVIGATION SIGNAL LIGHT

Double Deck Navigation Signal Light CXH-10P

ISO9001 Supplier

Class Certificate

Export Supply

The Navigation Signal Light used to the ship with length 50M or above as lamp signal liaison when night navigation.



Key Highlights

Category	Marine Navigation Signal Light
Standard	ISO
Material	Engineering Plastic, Steel, Stainless Steel
Weight / Size	Voltage 24V 110V 220V Power 60W 60W 60W Luminous Intensity 60cd Lamp Hol...
Certificate	CCS Type Approval Certificate

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Navigation Signal Light	Model / SKU	Double-Deck-Navigation-Signal-Light-CXH-10P
Standard	ISO	Material	Engineering Plastic, Steel, Stainless Steel
Weight / Size	Voltage 24V 110V 220V Power 60W 60W 60W Luminous Intensity 60cd Lamp Holder P28S Protection Class IP56 Cable Outside Diameter Dia.9 Name Type Visibility Level Arc Color Weight Starboard Light CXH1-10P 3n.m 112.5o Green 3.8KGS Port Light CXH2-10P 3n.m 112.5o Red 3.8KGS Masthead Light CXH3-10P 3n.m 225o White 3.7KGS Stern Light CXH4-10P 3n.m 135o White/Yellow 3.7KGS All-round-Light CXH6-10P 3n.m 360o Red/green/white 3.6KGS Navigation Signal Light CXH2-10P Supplied to India in 2016	Certificate	CCS Type Approval Certificate
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China Double Deck Navigation Signal Light CXH-10P:
- Navigation Signal Light CXH2-10P Supplied to India in 2016

China Double Deck Navigation Signal Light CXH-10P:

The Navigation Signal Light used to the ship with length 50M or above as lamp signal liaison when night navigation.

Product Advantages:

1. The signal lights have the seal structure, waterproof under the extreme environment.
2. The shell is made of high-strength engineering plastic PA+GF, the lamp shade use injection of PC, lens hood of good quality stainless steel
3. Special light bulb with average life up to 700hrs.
4. Working Temperature: -30°C-55°C





Standards:

1. Confirm to the international regulation for preventing collision at sea, 1972 and grade entry norms for steel ships.
2. Confirm to the International Standard IEC60598-1-2008.
3. Confirm to the standard of marine electric signal light's technical condition GB/T 3028-2012.

Main Specification:

Voltage	24V	110V	220V
Power	60W	60W	60W
Luminous Intensity	60cd		
Lamp Holder	P28S		
Protection Class	IP56		
Cable Outside Diameter	Dia.9		

Name	Type	Visibility	Level Arc	Color	Weight
Starboard Light	CXH1-10P	3n.m	112.5°	Green	3.8KGS
Port Light	CXH2-10P	3n.m	112.5°	Red	3.8KGS
Masthead Light	CXH3-10P	3n.m	225°	White	3.7KGS
Stern Light	CXH4-10P	3n.m	135°	White/Yellow	3.7KGS
All-round- Light	CXH6-10P	3n.m	360°	Red/green/white	3.6KGS

Navigation Signal Light CXH2-10P Supplied to India in 2016

