


MARINE NAVIGATION SIGNAL LIGHT

Double-Deck Stainless Steel Navigation Signal Light CXH-20S

- ISO9001 Supplier
- Class Certificate
- Export Supply

The Navigation Signal Light used to the ship with length 12M or above as lamp signal liaison when night navigation.

	Key Highlights	
	Category	Marine Navigation Signal Light
	Standard	ISO
	Material	Stainless Steel
	Weight / Size	Voltage 24V Power 2X30W Lamp Holder P28S Protection Class IP56 Cable Di...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	
<p>We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.</p>		

Technical Specifications			
Category	Marine Navigation Signal Light	Model / SKU	Double-Deck-Stainless-Steel- Navigation-Signal-Light-CXH-20S
Standard	ISO	Material	Stainless Steel
Weight / Size	Voltage 24V Power 2X30W Lamp Holder P28S Protection Class IP56 Cable Diameter Dia.8 Name Type Visibility Level Arc Color Weight Starboard Light CXH1-20S 2n.m 112.5o Green 1.5KGS Port Light CXH2-20S 2n.m 112.5o Red 1.5KGS Masthead Light CXH3-20S 5n.m 225o White 1.4KGS Stern Light CXH4-20S 2n.m 135o White/Yellow 1.4KGS All-round-Light CXH6-20S 2n.m 360o Red/green/white 1.3KGS	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	<ul style="list-style-type: none"> ■ China Double-Deck Stainless Steel Navigation Signal Light CXH-20S: ■ Standards: 	<ul style="list-style-type: none"> ■ Product Advantage: ■ Main Specification:
-----------------	--	---

China Double-Deck Stainless Steel Navigation Signal Light CXH-20S:



The Navigation Signal Light used to the ship with length 12M or above as lamp signal liaison when night navigation.

Product Advantage:

1. Easy to Install and replace the bulb with a leakage hole at the bottom.
2. The shell is made of stainless steel, corrosion resistance and impact resistance.

3. The shade is made of polycarbonate, UV Resistance and non-discolouring color.

Standards:

1. Confirm to the international regulation for preventing collision at sea, 1972 and grade entry norms for steel ships.
2. Confirm to the International Standard IEC60598-1-2008.
3. Confirm to the standard of marine electric signal light's technical condition GB/T 3028-2012.

Main Specification:

Voltage	24V
Power	2X30W
Lamp Holder	P28S
Protection Class	IP56
Cable Diameter	Dia.8

Name	Type	Visibility	Level Arc	Color	Weight
Starboard Light	CXH1-20S	2n.m	112.5°	Green	1.5KGS
Port Light	CXH2-20S	2n.m	112.5°	Red	1.5KGS
Masthead Light	CXH3-20S	5n.m	225°	White	1.4KGS
Stern Light	CXH4-20S	2n.m	135°	White/Yellow	1.4KGS
All-round- Light	CXH6-20S	2n.m	360°	Red/green/white	1.3KGS