BREATHER VALVE

Double Nozzles Flame Arrester Breather Valve

ISO9001 Supplier

Class Certificate

Export Supply

We can supply all kinds of Flame Arrester Breather Valve,High quality, Fast Delivery; Customized Service available



Key Highlights

Category	Breather Valve
Standard	EN
Material	304,316, Aluminum Alloy
Weight / Size	Material Component Body Stem Guide Pressure Disk Pressure Seat Gasket Fi...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Breather Valve	**Model / SKU**	Double-Nozzles-Flame-Arrester-Breather-Valve
Standard	EN	**Material**	304,316, Aluminum Alloy
Weight / Size	Material Component Body Stem Guide Pressure Disk Pressure Seat Gasket Fire Arresting Material Steel 304 304 304 304 304 Aluminums 316 316 316 316 316 Casting 316L 316L 316L 316L 316L - PTFE PTFE PTFE PTFE PTFE Installation Size DN 25 32 40 50 80 100 150 200 250 300 L 280 300 320 320 450 450 620 750 850 1100 H 300 320 350 350 500 500 600 700 820 900	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

CONTENTS

- China Double Nozzles Flame Arrester Breather Valve:
- Material
- Installation Size

China Double Nozzles Flame Arrester Breather Valve:

Double Nozzles Flame Arrester Breather Valve is fixed installed in the indoor at the top of suction of the tank for fire breathing function, it can automatic adjustment of pressure from inside and outside, which has the feature of reliable performance, stability and in line with the ministry of petroleum industry SY7511-87 standard.

Material

Component	Body	Stem Guide	Pressure Disk	Pressure Seat	Gasket	Fire Arresting
Material	Steel	304	304	304	304	304
	Aluminums	316	316	316	316	316
	Casting	316L	316L	316L	316L	316L
	-	PTFE	PTFE	PTFE	PTFE	PTFE

Installation Size

DN	25	32	40	50	80	100	150	200	250	300
L	280	300	320	320	450	450	620	750	850	1100
H	300	320	350	350	500	500	600	700	820	900