

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

DREDGING RUBBER HOSE

Dredge Discharge Hose

Steel Flange Discharge Hose are used with dredger for silt, gravel conceyance. Thickness of pipe wall is from 18mm to 70mm. Working Temperature is from -20Degree to 50Degree. Easy Install, Flexi...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Dredging Rubber Hose
Standard	DIN
Material	NR, SBR, BR
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Dredging Rubber Hose	Model / SKU	Dredge-Discharge-Hose
Standard	DIN	Material	NR, SBR, BR
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- China Dredge Discharge Hose:

- Specification

China Dredge Discharge Hose:

Steel Flange Discharge Hose are used with dredger for silt, gravel conceyance. Thickness of pipe wall is from 18mm to 70mm.

- Working Temperature is from -20Degree to 50Degree.
- Easy Install, Flexible to use, Safe, Abrasion-resistance and bending resistant.
- Safety Factor: 1:5
- Hose Ling: NR, SBR, BR



- Reinforcement Layer: Tire Cord with Wire Spiral
- Cover Rubber Layer: SBR and CR Blend.

Specification

ID		OD		WP		BP		VP		Length
mm	inch	mm	inch	Mpa	bar	Mpa	bar	Kpa	bar	m
152	6"	182	7-1/4"	1.2	12	2.4	24	80	0.8	20
203	8"	233	9-1/5"	1.2	12	2.4	24	80	0.8	20
254	10"	284	11-1/5"	1	10	2	20	80	0.8	10
304	12"	340	13-2/5"	1	10	2	20	80	0.8	6-10
350	14"	390	15-2/5"	1	10	2	20	80	0.8	6-10
450	18"	486	19-1/5"	0.7	7	1.5	15	80	0.8	6-10
550	22"	590	23-3/5"	0.7	7	1.5	15	80	0.8	6-10
600	24"	640	25-3/5"	0.7	7	1.5	15	80	0.8	6-10
700	28"	750	29-3/5"	0.7	7	1.5	15	80	0.8	6-10
800	32"	850	33-1/2"	0.5	5	1	10	80	0.8	6-10
1000	40"	1050	41-1/2"	0.5	5	1	10	80	0.8	6
1200	48"	1250	49-1/5"	0.5	5	1	10	80	0.8	6
1300	52"	1350	53-1/5"	0.5	5	1	10	80	0.8	6