DREDGING RUBBER HOSE

# Dredge Discharge Hose

Steel Flange Discharge Hose are used with dredger for silt, gravel conceyance. Thickness of pipe wall is from 18mm to 70mm. Working Temperature is from -20Degree to 50Degree. Easy Install, Flexi...

ISO9001 Supplier

Class Certificate

Export Supply




## Key Highlights

| | |
|---|---|
| **Category** | Dredging Rubber Hose |
| **Standard** | DIN |
| **Material** | NR, SBR, BR |
| **Certificate** | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

## Technical Specifications

| | | | |
|---|---|---|---|
| **Category** | Dredging Rubber Hose | **Model / SKU** | Dredge-Discharge-Hose |
| **Standard** | DIN | **Material** | NR, SBR, BR |
| **Certificate** | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS | **Warranty** | 12 Months unless specified otherwise |
| **Origin** | China | | |

**CONTENTS**

- China Dredge Discharge Hose:
- Specification

## China Dredge Discharge Hose:

Steel Flange Discharge Hose are used with dredger for silt, gravel conceyance. Thickness of pipe wall is from 18mm to 70mm.

- Working Temperature is from -20Degree to 50Degree.
- Easy Install, Flexible to use, Safe, Abrasion-resistance and bending resistant.
- Safety Factor: 1:5
- Hose Ling: NR, SBR, BR

- Reinforcement Layer: Tire Cord with Wire Spiral
- Cover Rubber Layer: SBR and CR Blend.

## Specification

| ID | | OD | | WP | | BP | | VP | | Length |
|---|---|---|---|---|---|---|---|---|---|---|
| mm | inch | mm | inch | Mpa | bar | Mpa | bar | Kpa | bar | m |
| 152 | 6" | 182 | 7-1/4" | 1.2 | 12 | 2.4 | 24 | 80 | 0.8 | 20 |
| 203 | 8" | 233 | 9-1/5" | 1.2 | 12 | 2.4 | 24 | 80 | 0.8 | 20 |
| 254 | 10" | 284 | 11-1/5" | 1 | 10 | 2 | 20 | 80 | 0.8 | 10 |
| 304 | 12" | 340 | 13-2/5" | 1 | 10 | 2 | 20 | 80 | 0.8 | 6-10 |
| 350 | 14" | 390 | 15-2/5" | 1 | 10 | 2 | 20 | 80 | 0.8 | 6-10 |
| 450 | 18" | 486 | 19-1/5" | 0.7 | 7 | 1.5 | 15 | 80 | 0.8 | 6-10 |
| 550 | 22" | 590 | 23-3/5" | 0.7 | 7 | 1.5 | 15 | 80 | 0.8 | 6-10 |
| 600 | 24" | 640 | 25-3/5" | 0.7 | 7 | 1.5 | 15 | 80 | 0.8 | 6-10 |
| 700 | 28" | 750 | 29-3/5" | 0.7 | 7 | 1.5 | 15 | 80 | 0.8 | 6-10 |
| 800 | 32" | 850 | 33-1/2" | 0.5 | 5 | 1 | 10 | 80 | 0.8 | 6-10 |
| 1000 | 40" | 1050 | 41-1/2" | 0.5 | 5 | 1 | 10 | 80 | 0.8 | 6 |
| 1200 | 48" | 1250 | 49-1/5" | 0.5 | 5 | 1 | 10 | 80 | 0.8 | 6 |
| 1300 | 52" | 1350 | 53-1/5" | 0.5 | 5 | 1 | 10 | 80 | 0.8 | 6 |