

# Jinbo Marine

Marine & Offshore Equipment Datasheet


**PRODUCT DATASHEET**

**DREDGING RUBBER HOSE**

## Dredge Sunction Hose

The steel flnage suction hose are used with dredger fro silt, gravel conveyance. Thickness of pipe wall is from 32mm to 58mm Working Temperature is from -20Degree to 50Degree. Easy Install, Flex...

- ISO9001 Supplier
- Class Certificate
- Export Supply



### Key Highlights

<b>Category</b>	Dredging Rubber Hose
<b>Standard</b>	DIN
<b>Material</b>	NR, SBR, BR
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
<b>Category</b>	Dredging Rubber Hose	<b>Model / SKU</b>	Dredge-Sunction-Hose
<b>Standard</b>	DIN	<b>Material</b>	NR, SBR, BR
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	<b>Warranty</b>	12 Months unless specified otherwise
<b>Origin</b>	China		

<b>CONTENTS</b>	■ China Dredge Sunction Hose:	■ Suction Hose Specification
-----------------	-------------------------------	------------------------------

### China Dredge Sunction Hose:

The steel flnage suction hose are used with dredger fro silt, gravel conveyance. Thickness of pipe wall is from 32mm to 58mm

- Working Temperature is from -20Degree to 50Degree.
- Easy Install, Flexible to use, Safe, Abrasion-resistance and bending resistant.
- Safety Factor: 1:5
- Hose Ling: NR, SBR, BR

- Reinforcement Layer: Tire Cord with Wire Spiral
- Cover Rubber Layer: SBR and CR.

## Suction Hose Specification

ID		OD		WP		BP		VP		Length
mm	inch	mm	inch	Mpa	bar	Mpa	bar	Kpa	bar	m
152	6"	182	7-1/4"	1.2	12	2.4	24	80	0.8	20
203	8"	233	9-1/5"	1.2	12	2.4	24	80	0.8	20
254	10"	284	11-1/5"	1	10	2	20	80	0.8	10
304	12"	340	13-2/5"	1	10	2	20	80	0.8	6-10
350	14"	390	15-2/5"	1	10	2	20	80	0.8	6-10
450	18"	486	19-1/5"	0.7	7	1.5	15	80	0.8	6-10
550	22"	590	23-3/5"	0.7	7	1.5	15	80	0.8	6-10
600	24"	640	25-3/5"	0.7	7	1.5	15	80	0.8	6-10
700	28"	750	29-3/5"	0.7	7	1.5	15	80	0.8	6-10
800	32"	850	33-1/2"	0.5	5	1	10	80	0.8	6-10
1000	40"	1050	41-1/2"	0.5	5	1	10	80	0.8	6
1200	48"	1250	49-1/5"	0.5	5	1	10	80	0.8	6
1300	52"	1350	53-1/5"	0.5	5	1	10	80	0.8	6