DREDGING RUBBER HOSE

Dredging Discharging And Suction Hose

ISO9001 Supplier

Class Certificate

Export Supply

Dredging Discharging And Suction hose General description The steel flange discharge hoses are used with dredgers for silt/gravels conveyance. Thickness of the pipe wall is from 18mm to 70mm. The s...



Key Highlights

Category	Dredging Rubber Hose
Standard	DIN
Material	Dredging Discharging And Suction hose General description The steel flan...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Dredging Rubber Hose	**Model / SKU**	Dredging-Discharging-And-Suction-Hose
Standard	DIN	**Material**	Dredging Discharging And Suction hose General description The steel flange discharge hoses are used with dredgers for silt/gravels conveyance.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS

- Dredging Discharging And Suction hose
- General description
- Performance For discharging hose
- Performance for suction hose

Dredging Discharging And Suction hose

General description

The steel flange discharge hoses are used with dredgers for silt/gravels conveyance. Thickness of the pipe wall is from 18mm to 70mm. The suitable working temperature is from -20c to 50c. It is convenient to install, flexible to use, safe, abrasion-resistant and bending-resistant.

Other technical parameter can be made according to the client’s requirement.

Performance For discharging hose

Inner diameter		Working pressure	Burst pressure	Length	Thickness of the pipe wall
mm	Tolerance(mm)	Mpa	Mpa	M	mm
300	+/-2	0.4-1.2	3.6	1-3	34-37
414	+/-2	0.4-1.2	3.6	1-3	35-37
560	+/-3	0.4-1.2	3.6	2-3	40-45
600	+/-3	0.4-1.2	3.6	2-3	40-45
700	+/-3	0.8-1.5	4.5	2-3	40-45
800	+/-5	1.2-2.5	5.5	2-3	50-52
900	+/-5	1.5-2.5	7.5	2-3	55-58
1000	+/-5	2.0-2.5	7.5	3-5	75

Performance for suction hose

Inner diameter		Working pressure	Length	Thickness of the pipe wall
mm	Tolerance(mm)	Mpa	M	mm

250	+/2	60mm Mercury Max vac 650mm high	1-3	31-32
300	+/2		1-3	34-37
414	+/2		1-3	35-37
560	+/3		2-3	40-45
600	+/3		2-3	40-45
700	+/3		2-3	40-45
800	+/4		2-3	50-52
900	+/4		2-3	55-58