

DREDGING RUBBER HOSE

# Dredging Discharging And Suction Hose

ISO9001 Supplier

Class Certificate

Export Supply

Dredging Discharging And Suction hose General description The steel flange discharge hoses are used with dredgers for silt/gravels conveyance. Thickness of the pipe wall is from 18mm to 70mm. The s...



## Key Highlights

<b>Category</b>	Dredging Rubber Hose
<b>Standard</b>	DIN
<b>Material</b>	Dredging Discharging And Suction hose General description The steel flan...
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

## Technical Specifications

<b>Category</b>	Dredging Rubber Hose	<b>Model / SKU</b>	Dredging-Discharging-And-Suction-Hose
<b>Standard</b>	DIN	<b>Material</b>	Dredging Discharging And Suction hose General description The steel flange discharge hoses are used with dredgers for silt/gravels conveyance.
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	<b>Warranty</b>	12 Months unless specified otherwise
<b>Origin</b>	China		

**CONTENTS**

- Dredging Discharging And Suction hose
- Performance For discharging hose
- General description
- Performance for suction hose

## Dredging Discharging And Suction hose

### General description

The steel flange discharge hoses are used with dredgers for silt/gravels conveyance. Thickness of the pipe wall is from 18mm to 70mm. The suitable working temperature is from -20c to 50c. It is convenient to install, flexible to use, safe, abrasion-resistant and bending-resistant.

Other technical parameter can be made according to the client's requirement.

### Performance For discharging hose

Inner diameter		Working pressure	Burst pressure	Length	Thickness of the pipe wall
mm	Tolerance(mm)	Mpa	Mpa	M	mm
300	+/-2	0.4-1.2	3.6	1-3	34-37
414	+/-2	0.4-1.2	3.6	1-3	35-37
560	+/-3	0.4-1.2	3.6	2-3	40-45
600	+/-3	0.4-1.2	3.6	2-3	40-45
700	+/-3	0.8-1.5	4.5	2-3	40-45
800	+/-5	1.2-2.5	5.5	2-3	50-52
900	+/-5	1.5-2.5	7.5	2-3	55-58
1000	+/-5	2.0-2.5	7.5	3-5	75

### Performance for suction hose

Inner diameter		Working pressure	Length	Thickness of the pipe wall
mm	Tolerance(mm)	Mpa	M	mm

250	+/2	60mm Mercury Max vac 650mm high	1-3	31-32
300	+/2		1-3	34-37
414	+/2		1-3	35-37
560	+/3		2-3	40-45
600	+/3		2-3	40-45
700	+/3		2-3	40-45
800	+/4		2-3	50-52
900	+/4		2-3	55-58