ABRASIVE MATERIAL RUBBER HOSE

# Dry Cement Hose

Used casting, steel, stone, sand, cement and other abrasive amterial in sandblacking service Characteristics: high tensile; wear, weather, ozone and aging resistance Working temperature: -20 TO 80...

ISO9001 Supplier

Class Certificate

Export Supply




## Key Highlights

| | |
|---|---|
| **Category** | Abrasive Material Rubber Hose |
| **Standard** | EN |
| **Material** | Used casting, steel, stone, sand, cement and other abrasive amterial in ... |
| **Weight / Size** | 1:3 Main Specification ID OD Length Bend radium WP Weight in mm in mm ft... |
| **Certificate** | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

| Technical Specifications | | | |
|---|---|---|---|
| **Category** | Abrasive Material Rubber Hose | **Model / SKU** | Dry-Cement-Hose |
| **Standard** | EN | **Material** | Used casting, steel, stone, sand, cement and other abrasive amterial in sandblacking service Characteristics: |
| **Weight / Size** | 1:3 Main Specification ID OD Length Bend radium WP Weight in mm in mm ft m in mm Psi Kg/cm² Kg/m 1 25.4 1.701 43.2 200 60 6 150 200 15 1.38 1 1/4 31.8 1.953 49.6 200 60 8 200 200 15 1.6 1 1/2 38.1 2.232 56.7 200 60 10 250 200 15 1.91 2 50.8 2.772 70.4 200 60 12 300 150 10 2.6 2 1/2 63.5 3.272 83.1 200 60 15 375 150 10 3.1 3 76.2 3.811 96.8 200 60 20 500 150 10 3.95 4 101.6 5.047 128.2 200 60 28 700 150 10 6.48 5 127 6.091 154.7 100 30 40 1000 150 10 8.48 6 152.4 7.177 182.3 100 30 48 1200 150 10 11.07 8 203.2 9.268 235.4 100 30 64 1600 150 10 16.28 10 254 11.63 295.4 100 30 100 2500 100 7 26.05 12 304.8 13.866 352.2 100 30 120 3000 100 7 35.98 | **Certificate** | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |
| **Warranty** | 12 Months unless specified otherwise | **Origin** | China |

**CONTENTS**


- China Dry Cement Hose:
- Main Specification


## China Dry Cement Hose:

- Used casting, steel, stone, sand, cement and other abrasive amterial in sandblacking service
- Characteristics: high tensile; wear, weather, ozone and aging resistance
- Working temperature: -20 TO 80℃
- Safety Factor: 1:3

## Main Specification

| ID | | OD | | Length | | Bend radium | | WP | | Weight |
|---|---|---|---|---|---|---|---|---|---|---|
| in | mm | in | mm | ft | m | in | mm | Psi | Kg/cm² | Kg/m |
| 1 | 25.4 | 1.701 | 43.2 | 200 | 60 | 6 | 150 | 200 | 15 | 1.38 |

| | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| 1 1/4 | 31.8 | 1.953 | 49.6 | 200 | 60 | 8 | 200 | 200 | 15 | 1.6 |
| 1 1/2 | 38.1 | 2.232 | 56.7 | 200 | 60 | 10 | 250 | 200 | 15 | 1.91 |
| 2 | 50.8 | 2.772 | 70.4 | 200 | 60 | 12 | 300 | 150 | 10 | 2.6 |
| 2 1/2 | 63.5 | 3.272 | 83.1 | 200 | 60 | 15 | 375 | 150 | 10 | 3.1 |
| 3 | 76.2 | 3.811 | 96.8 | 200 | 60 | 20 | 500 | 150 | 10 | 3.95 |
| 4 | 101.6 | 5.047 | 128.2 | 200 | 60 | 28 | 700 | 150 | 10 | 6.48 |
| 5 | 127 | 6.091 | 154.7 | 100 | 30 | 40 | 1000 | 150 | 10 | 8.48 |
| 6 | 152.4 | 7.177 | 182.3 | 100 | 30 | 48 | 1200 | 150 | 10 | 11.07 |
| 8 | 203.2 | 9.268 | 235.4 | 100 | 30 | 64 | 1600 | 150 | 10 | 16.28 |
| 10 | 254 | 11.63 | 295.4 | 100 | 30 | 100 | 2500 | 100 | 7 | 26.05 |
| 12 | 304.8 | 13.866 | 352.2 | 100 | 30 | 120 | 3000 | 100 | 7 | 35.98 |