

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

OTHER MARINE VALVES & ACCESSORIES

Duplex Oil Tank Breather Valve CB/T692-94

ISO9001 Supplier

Class Certificate

Export Supply

Oil-Tank Breather Valve CB/T692-94 has simplex type and duplex type. Simplex oil tank breather valve is spring type, duplex oil tank breather valve is gravity type. When the pressure in the tank exceeds atmospheric ...



Key Highlights

Category	Other Marine Valves & Accessories
Standard	GB
Material	Cast Steel or Cast Iron
Weight / Size	Body/Bonnet---Cast Steel or Cast Iron Guide Rod---Stainless Steel Stem---...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Other Marine Valves & Accessories	Model / SKU	Duplex-Oil-Tank-Breather-Valve-CB-T692-94
Standard	GB	Material	Cast Steel or Cast Iron
Weight / Size	Body/Bonnet---Cast Steel or Cast Iron Guide Rod---Stainless Steel Stem---Bronze Main Size(mm):	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China Duplex Oil Tank Breather Valve CB/T692-94:
- Main Parts & Material:
- Technical Specification:
- Main Size(mm):

100/150	290	500	136	25	300	500	140	304	9	7
---------	-----	-----	-----	----	-----	-----	-----	-----	---	---

Type A and B:

nominal diameter	flange dimension														weight(kg)			
	oil-Tank connection flange					bolt		outlet flange					bolt		cast iron		cast steel	
	D	D1	D2	b	d0	n	Th.	D1	D11	D21	b1	d01	n	Th.	A	B	A	B
80/100	170	138	118	14	15	8	M14	190	158	138	14	15	8	M14	25.7	53.54	23.26	50.1
100/150	190	158	138	14	15	8	M14	240	208	190	14	15	12	M14	38.32	38.32	35.54	81.96

Type AS, BS:

nominal diameter	flange dimension														weight(kg)			
	oil-Tank connection flange					bolt		outlet flange					bolt		cast iron		cast steel	
	D	D1	D2	b	d0	n	Th.	D1	D11	D21	b1	d01	n	Th.	AS	BS	AS	BS
80/100	190	158	128	18	18	4	M16	210	170	148	18	18	4	M16	29.97	58.28	28.86	57.40
100/150	210	170	148	18	18	4	M16	265	225	202	20	18	8	M16	44.86	93.92	43.05	91.46