

Brushless high power motor has convenient maintenance and long service life.

High performance radiator, when the oil temperature reaches 35 degrees, the fan starts automatically, so that it can work without interruption for a long time.

The electric control box adopts integrated circuits, and can be equipped with hydraulic machines, such as hydraulic cylinders, wrenches, hydraulic tongs, etc.

Model	Output Port	Power Parameter	(MPa) Working Pressure		(L/min) Flow		Tank Volume (L)	Outer Size (LXWXH) (mm)	Reference Weight (KG)
			High Pressure	Low Pressure	High Pressure	low Pressure			
EMP204 X-2	4X1/4 NPT	220V/1.1 KW	70	6	0.8	6	7.6	394x300x420	27
EMP204 X-4	8X1/4 NPT	220V/1.1 KW	70	6	0.8	6	7.6	394x300x420	27.5
EMP204 -1	2X1/4 NPT	220V/1.5 KW	70	6	1.1	6	8	450x325x540	36
EMP204 - 2	4X1/4 NPT	220V/1.5 KW	70	6	1.1	6	8	450x325x540	36.5
EMP204 -4	8X1/4 NPT	220V/1.5 KW	70	6	1.1	6	8	450x325x540	37
EMP204 -380-1	2X1/4 NPT	380V/1.5 KW	70	6	1.1	6	8	450x325x540	36
EMP204 -380-2	4X1/4 NPT	380V/1.5 KW	70	6	1.1	6	8	450x325x540	36.5
EMP204 -380-4	8X1/4 NPT	380V/1.5 KW	70	6	1.1	6	8	450x325x540	37