

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

RUBBER SHEET

EPDM Rubber Sheet

CR Neoprene Rubber Sheet Specification: 0.8 to 50mm thickness. 0.2 to 3 m width. 1 to 20 m length. Density:1.3 to 1.5g/cm³ . Tensile strength: 500 to 1500psi Elongation: 300% to 400% Hardnes...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Rubber Sheet
Standard	EN
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Rubber Sheet	Model / SKU	EPDM-Rubber-Sheet
Standard	EN	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China EPDM Rubber Sheet:
- Application:
- Features:

China EPDM Rubber Sheet:

CR Neoprene Rubber Sheet

Specification: 0.8 to 50mm thickness. 0.2 to 3 m width. 1 to 20 m length.

Density:1.3 to 1.5g/cm³ .

Tensile strength: 500 to 1500psi



Elongation: 300% to 400%

Hardness:40 to 80 ±5 Shore-A

Application:

Suitable for gaskets,sealing,O rings, washer.

Used in Mining industry.

Waterproof in bridge construction and roof.

To be used as door.

Features:

Corrosion resistant, industrial oil, industrial acid and alkali heat.

Excellent Ozone, aging resistance.

Waterproof.

Temperature resistance.

Good resistant to mineral acids,alkali,steam,abrasion and heat. Anti-shock and oil resistant.

Good ultraviolet resisting.