

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

MARINE WINDLASS

Electric Combined Windlass

Electric Combined Windlass General description The combined and capstan are for heaving, launching and mooring, which are in accordance with ISO4568-1986<math>\lt;math>. They are driven by hand, elec...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Windlass
Standard	ISO
Material	Cast steel
Certificate	CCS , Rina , ABS, BV, GL,

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Windlass	Model / SKU	Electric-Combined-Windlass
Standard	ISO	Material	Cast steel
Certificate	CCS , Rina , ABS, BV, GL,	Warranty	12 Months unless specified otherwise
Origin	China		

China Electric Combined Windlass:

Electric Combined Windlass

General description

The combined and capstan are for heaving, launching and mooring, which are in accordance with ISO4568-1986<math>\lt;math>. They are driven by hand, electric, hydraulic and diesel engine. The structure types are divided into: systematic double-chain anchor winch (A type);single-chain anchor winch(B type) anchor capstan(E type).

Type illustration

The first letter: D-electric Y-hydraulic S-manual C-diesel engine



The letter M: anchor winch

The third letter: Type A,B,E

Main technical parameter

Type	anchor chain diam	working load		over loading		loading support		nominal speed	Drum load	Nominal speed	Cable capacity	Mooring line load
		A M 3	A M 2	A M 3	A M 2	A M 3	m / min					
(mm)	AM2	A M 3	A M 2	A M 3	A M 2	A M 3	m / min	Kn	m/min	m	Kn	
DMA-17.5	17.5	13	14.6	19.5	21.9	80	115	9	10	10	Φ11x100	8
DMA-19	19	15.3	17.2	23	25.8	95	135	9	15	10	Φ13x100	10
DMA-20	20	17.9	20	26.9	30	110	157	9	20	10	Φ13x100	10
DMA-22	22	20.6	23	30.9	34.5	126	180	9	20	15	Φ15x100	15
DMA-24	24	24.5	27.4	36.8	41.1	149	214	9	20	15	Φ15x100	20
DMA-26	26	27.7	31.1	41.1	45.2	175	250	9	20	10	Φ22x100	20
DMA-28	28	33.3	37.2	49.8	55.8	218	309	9	20	10	Φ22x120	20
DMA-30	30	38.3	42.8	56.5	62.2	253	350	9	30	10	Φ22x120	30
DMA-32	32	43.5	48.6	63.3	69.9	296	414	9	30	9	Φ20x120	30
DMA-34	34	49.1	54.9	71.3	78.4	344	481	9	40	9	Φ20x120	30
DMA-36	36	55.1	61.6	79.7	87.4	409	570	9	30	12	Φ20x120	30

DMA-38	38	6 1. 4	6 8. 9	9 2. 1	1 0 3. 4	3 6 5	5 2 2	9	40	15	Φ22x150	40
DMA-40	40	6 8	7 6	1 0 2	1 1 4	4 0 2	5 7 6	9	40	9	Φ22x150	40
DMA-42	42	7 5	8 3. 8	1 1 2. 5	1 2 5. 7	4 4 2	6 3 2	9	40	15	Φ22x150	50
DMA-44	44	8 2. 3	9 2	1 2 3. 5	1 3 8	4 8 3	6 9 1	9	50	15	Φ26x200	50
DMA-46	46	8 9. 9	1 0 0. 5	1 3 4. 9	1 5 0. 8	5 2 6	7 5 3	9	50	18	Φ26x200	50
DMA-48	48	9 7. 9	1 0 9. 4	1 4 6. 9	1 6 4. 1	5 7 0	8 1 6	9	60	10	Φ26x200	50
DMA-50	50	1 0 6. 3	1 1 8. 8	1 5 9. 5	1 7 8. 2	6 1 7	8 8 2	9	80	15	Φ26x200	50