MARINE WINCH

Electric Logging Winch

ISO9001 Supplier

Class Certificate

Export Supply

Electric Logging Winch Description: DCJ Electric Logging Winch is mainly applied in the measurement of petroleum wells (vertical, directional, cluster), by lifting and lowering measurement instruments to o...



Key Highlights

Category	Marine Winch
Standard	EN
Weight / Size	Technical Specification: Electric Power(KW) 4-7.8 Logging Depth(m) 4000...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Winch	**Model / SKU**	Electric-Logging-Winch
Standard	EN	**Weight / Size**	Technical Specification: Electric Power(KW) 4-7.8 Logging Depth(m) 4000-7000 Roller Speed(R/min) 15-150 Max Lifting Weight(KG) 80 Dimensions Length(mm) 859 Width(mm) 920 Height(mm) 975 Wire diameter(mm) 2.2-2.5 Weight(KG) 430
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS

- Electric Logging Winch
- Features:
- Description:
- Technical Specification:

Electric Logging Winch

Description:

DCJ Electric Logging Winch is mainly applied in the measurement of petroleum wells (vertical, directional, cluster), by lifting and lowering measurement instruments to obtain the gradient, location and depth of the wells. It is driven by the electromagnetic governor motor, transferring torque to the drum through sprockets, equipping with speed controller to control the rotary speed of the drum. It is ideal equipment for logging petroleum wells.

Features:

- Automatic spooling device.
- Simple brake device is easy to operate and reliable to use.
- Wide range of speed control and high precision.
- Automatically show the depth and easy to reset.

Technical Specification:

Electric Power(KW)		4-7.8
Logging Depth(m)		4000-7000
Roller Speed(R/min)		15-150
Max Lifting Weight(KG)		80
Dimensions	Length(mm)	859
	Width(mm)	920
	Height(mm)	975
Wire diameter(mm)		2.2-2.5
Weight(KG)		430