

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

## FIRE MONITOR

# Electrical Fire Monitor 30-80L/S

TYPE: JBPSKD30-80 Flow Range: 30-80L/S Automatic Nozzle Working Pressure: 6 bar~ 10 bar Max Reach @ Max Flow: 85m Max. Range of motion: +/-90°Vert , 350°Rot Max fog angle : 120° Turning speed : 18 degrees/sec Materia...

ISO9001 Supplier

Class Certificate

Export Supply



## Key Highlights

Category	Fire Monitor
Standard	EN
Material	+/-90°Vert , 350°Rot Max fog angle : 120° Turning speed : 18 degrees/sec Ma...
Weight / Size	+/-90°Vert , 350°Rot Max fog angle : 120° Turning speed : 18 degrees/sec Ma...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
<b>Category</b>	Fire Monitor	<b>Model / SKU</b>	Electrical-Fire-Monitor-30-80L-S
<b>Standard</b>	EN	<b>Material</b>	+/-90°Vert , 350°Rot Max fog angle : 120° Turning speed : 18 degrees/sec Material (body) : 304L Stainless Steel, 316L Stainless Steel is also available Material (Gear) : hardcoated anodizing aluminum Material (nozzle) : Aluminum power supply : 12/24VDC or 100-230VAC Power Consumption normal/Max : 50W/150W Weight incl.
<b>Weight / Size</b>	+/-90°Vert , 350°Rot Max fog angle : 120° Turning speed : 18 degrees/sec Material (body) : 304L Stainless Steel, 316L Stainless Steel is also available Material (Gear) : hardcoated anodizing aluminum Material (nozzle) : Aluminum power supply : 12/24VDC or 100-230VAC Power Consumption normal/Max : 50W/150W Weight incl.	<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
<b>Warranty</b>	12 Months unless specified otherwise	<b>Origin</b>	China

## China Electrical Fire Monitor 30-80L/S:

TYPE: JBPSKD30-80  
 Flow Range: 30-80L/S Automatic Nozzle  
 Working Pressure: 6 bar~ 10 bar  
 Max Reach @ Max Flow: 85m  
 Max. Range of motion: +/-90°Vert , 350°Rot  
 Max fog angle : 120°  
 Turning speed : 18 degrees/sec  
 Material (body) : 304L Stainless Steel, 316L Stainless Steel is also available  
 Material (Gear) : hardcoated anodizing aluminum  
 Material (nozzle) : Aluminum  
 power supply : 12/24VDC or 100-230VAC  
 Power Consumption normal/Max : 50W/150W  
 Weight incl. nozzle : appox 28kg  
 Cable Length Monitor- CPU : 5m  
 Cable Length Joystick-CPU : 5m standard/ other length available  
 Pump requirement for minimum performance : 80L/S@ 8 bar  
 Pipe dimensions for installation: 3 Inch



Monitor Inlet : 3" male BSP or DN100 flange

Monitor Outlet : 2.5 inch (65mm)

Water way size: 3 inch

PACKAGE: SS MONITOR, NOZZLE, CONTROL BOX, JOYSTICK, CABLES, WIRELESS CONTROL