FIRE MONITOR

Electrical Fire Monitor 30-80L/S

ISO9001 Supplier

Class Certificate

Export Supply

TYPE: JBPSKD30-80 Flow Range: 30-80L/S Automatic Nozzle Working Pressure: 6 bar~ 10 bar Max Reach @ Max Flow: 85m Max. Range of motion: +/-90°Vert , 350°Rot Max fog angle ：120° Turning speed：18 degrees/sec Materia...



Key Highlights

Category	Fire Monitor
Standard	EN
Material	+/-90°Vert , 350°Rot Max fog angle ：120° Turning speed：18 degrees/sec Ma...
Weight / Size	+/-90°Vert , 350°Rot Max fog angle ：120° Turning speed：18 degrees/sec Ma...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Fire Monitor	**Model / SKU**	Electrical-Fire-Monitor-30-80L-S
Standard	EN	**Material**	+/-90°Vert , 350°Rot Max fog angle ：120° Turning speed：18 degrees/sec Material (body)：304L Stainless Steel, 316L Stainless Steel is also available Material (Gear)：hardcoated anodizing aluminum Material (nozzle)：Aluminum power supply：12/24VDC or 100-230VAC Power Consumption normal/Max：50W/150W Weight incl.
Weight / Size	+/-90°Vert , 350°Rot Max fog angle ：120° Turning speed：18 degrees/sec Material (body)：304L Stainless Steel, 316L Stainless Steel is also available Material (Gear)：hardcoated anodizing aluminum Material (nozzle)：Aluminum power supply：12/24VDC or 100-230VAC Power Consumption normal/Max：50W/150W Weight incl.	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

China Electrical Fire Monitor 30-80L/S:

TYPE: JBPSKD30-80
Flow Range: 30-80L/S Automatic Nozzle
Working Pressure: 6 bar~ 10 bar
Max Reach @ Max Flow: 85m
Max. Range of motion: +/-90°Vert , 350°Rot
Max fog angle ：120°
Turning speed：18 degrees/sec
Material (body)：304L Stainless Steel, 316L Stainless Steel is also available
Material (Gear)：hardcoated anodizing aluminum
Material (nozzle)：Aluminum
power supply：12/24VDC or 100-230VAC
Power Consumption normal/Max：50W/150W
Weight incl. nozzle：appox 28kg
Cable Length Monitor- CPU：5m
Cable Length Joystick-CPU：5m standard/ other length available
Pump requirement for minimum performance：80L/S@ 8 bar
Pipe dimensions for installation: 3 Inch

Monitor Inlet ：3” male BSP or DN100 flange
Monitor Outlet：2.5 inch (65mm)
Water way size: 3 inch
PACKAGE: SS MONITOR, NOZZLE, CONTROL BOX, JOYSTICK, CABLES, WIRELESS CONTROL