

MARINE EXPLOSION-PROOF LIGHTS SERIES

# Explosion-proof Button Box CFA-2-2

Main Specification: Voltage 550V/20A Explosion-Proof Mark Exe II CT6 Protection Class ...

- ISO9001 Supplier
- Class Certificate
- Export Supply




### Key Highlights

|                    |  |
|--------------------|--|
| <b>Category</b>    | Marine Explosion-proof Lights Series       |
| <b>Material</b>    | Aluminum                                   |
| <b>Certificate</b> | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

|                 |                                      |                    |  |
|-----------------|--------------------------------------|--------------------|--|
| <b>Category</b> | Marine Explosion-proof Lights Series | <b>Model / SKU</b> | Explosion-proof-Button-Box-CFA-2-2         |
| <b>Material</b> | Aluminum                             | <b>Certificate</b> | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |
| <b>Warranty</b> | 12 Months unless specified otherwise | <b>Origin</b>      | China                                      |



## Main Specification:

|                      |              |
|----------------------|--------------|
| Voltage              | 550V/20A     |
| Explosion-Proof Mark | Exe II CT6   |
| Protection Class     | IP56         |
| Material             | Aluminum     |
| Cable Diameter       | Dia10-12.5mm |

### Explosion Gland

| Screw Thread Specification | Cable Diameter | Protection Class |
|----------------------------|----------------|------------------|
| M20X1.5                    | Dia.11-14.3    | IP66/68          |
| M25X1.5                    | Dia.13-20.2    | IP66/68          |
| M32X1.5                    | Dia. 19-26.5   | IP66/68          |
| M40X1.5                    | Dia. 25-32.5   | IP66/68          |

### Armoured Cable

| Screw Thread Specification | Inside Diameter | Outside Diameter | Protection Class |
|----------------------------|-----------------|------------------|------------------|
| M20X1.5                    | Dia.11-14.3     | Dia.13-20.2      | IP66/68          |
| M20X1.5                    | Dia8-11         | Dia. 12-17       | IP66/68          |
| M25X1.5                    | Dia.13-20.2     | Dia. 19-26.5     | IP66/68          |
| M25X1.5                    | Dia.12-17       | Dia. 17-22       | IP66/68          |
| M32X1.5                    | Dia.19-26.5     | Dia. 25-32.5     | IP66/68          |
| M32X1.5                    | Dia.17-22       | Dia.23-28        | IP66/68          |
| M40X1.5                    | Dia. 25-32.5    | Dia. 31.5-42.3   | IP66/68          |
| M40X1.5                    | Dia. 23-28      | Dia.30.37        | IP66/68          |