MARINE EXPLOSION-PROOF LIGHTS SERIES

Explosion-proof Button Box CFA-2-2

Main Specification: Voltage 550V/20A Explosion-Proof Mark Exe II CT6 Protection Class ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Explosion-proof Lights Series
Material	Aluminum
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Explosion-proof Lights Series	Model / SKU	Explosion-proof-Button-Box-CFA-2-2
Material	Aluminum	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China



Main Specification:

Voltage	550V/20A
Explosion-Proof Mark	Exe II CT6
Protection Class	IP56
Material	Aluminum
Cable Diameterial	Dia10-12.5mm

Explosion Gland

Screw Thread Specification	Cable Diameter	Protection Class
M20X1.5	Dia.11-14.3	IP66/68
M25X1.5	Dia.13-20.2	IP66/68
M32X1.5	Dia. 19-26.5	IP66/68
M40X1.5	Dia. 25-32.5	IP66/68

Armoured Cable

Screw Thread Specification	Inside Diameter	Outside Diameter	Protection Class
M20X1.5	Dia.11-14.3	Dia.13-20.2	IP66/68
M20X1.5	Dia8-11	Dia. 12-17	IP66/68
M25X1.5	Dia.13-20.2	Dia. 19-26.5	IP66/68
M25X1.5	Dia.12-17	Dia. 17-22	IP66/68
M32X1.5	Dia.19-26.5	Dia. 25-32.5	IP66/68
M32X1.5	Dia.17-22	Dia.23-28	IP66/68
M40X1.5	Dia. 25-32.5	Dia. 31.5-42.3	IP66/68
M40X1.5	Dia. 23-28	Dia.30.37	IP66/68