

Jinbo Marine

Marine & Offshore Equipment Datasheet


PRODUCT DATASHEET

MARINE EXPLOSION-PROOF LIGHTS SERIES

Explosion-proof Fluorescent Light CFY20 CFY30 CFY40

- ISO9001 Supplier
- Class Certificate
- Export Supply

Used to cabin illumination in the hazardous area such as chemical factory, oil refinery, oil and gas plant with explosive gas environment.

	Key Highlights	
	Category	Marine Explosion-proof Lights Series
	Standard	EN
	Material	Stainless Steel
	Weight / Size	Type CFY20-2 CFY20-1 CFY30-2 CFY30-1 CFY40-2 CFY40-1 Explosion-proof Mar...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	
<p>We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.</p>		



Technical Specifications			
Category	Marine Explosion-proof Lights Series	Model / SKU	Explosion-proof-Fluorescent-Light-CFY20-CFY30-CFY40
Standard	EN	Material	Stainless Steel
Weight / Size	Type CFY20-2 CFY20-1 CFY30-2 CFY30-1 CFY40-2 CFY40-1 Explosion-proof Mark Exd II C T6 Voltage 220V/50Hz, 220V/60Hz, 110V/60Hz Power 2x20W 1x20W 2x30W 1x30W 2x40W 1x40W Lamp Holder G13 Protection Class IP56 IP56 IP56 IP56 IP56 IP56 Cable Diameter Dia13-14mm Weight 11.5kg 11.5kg 13.5kg 13.5kg 15kg 15kg	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	■ China Explosion-proof Fluorescent Light CFY20 CFY30 CFY40:	■ Main Specification:

China Explosion-proof Fluorescent Light CFY20 CFY30 CFY40:



Used to cabin illumination in the hazardous area such as chemical factory, oil refinery, oil and gas plant with explosive gas environment.

Main Specification:

Type	CFY20-2	CFY20-1	CFY30-2	CFY30-1	CFY40-2	CFY40-1
Explosion-proof Mark	Exd II C T6					
Voltage	220V/50Hz, 220V/60Hz, 110V/60Hz					



Power	2x20W	1x20W	2x30W	1x30W	2x40W	1x40W
Lamp Holder	G13					
Protection Class	IP56	IP56	IP56	IP56	IP56	IP56
Cable Diameter	Dia13-14mm					
Weight	11.5kg	11.5kg	13.5kg	13.5kg	15kg	15kg