

MARINE EXPLOSION-PROOF LIGHTS SERIES


Explosion-proof Fluorescent Pendant Light CFY22-2 CFY42-2

ISO9001 Supplier

Class Certificate

Export Supply

Used to cabin illumination in the hazardous area such as chemical factory, oil refinery, oil and gas plant with explosive gas environment.

	Key Highlights	
	Category	Marine Explosion-proof Lights Series
	Standard	EN
	Material	Aluminum Alloy
	Weight / Size	Type CFY22-2 CFY42-2 Explosion-proof Mark Exd II C T5 T5 Exd II C T5 Voltage...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	
<p>We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.</p>		

Technical Specifications			
Category	Marine Explosion-proof Lights Series	Model / SKU	Explosion-proof-Fluorescent-Pendant-Light-CFY22-2-CFY42-2
Standard	EN	Material	Aluminum Alloy
Weight / Size	Type CFY22-2 CFY42-2 Explosion-proof Mark Exd II C T5 Exd II C T5 Voltage 220V/50Hz,220V/60Hz,110V/60Hz Power 2x20W 2X40W Lamp Holder G13 Protection Class IP54 IP56 Cable Diameter Dia10-12.5mm Weight 6.8kg 14.8kg	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China



CONTENTS

- China Explosion-proof Fluorescent Pendant Light CFY22-2 CFY42-2:

- Main Specification:

China Explosion-proof Fluorescent Pendant Light CFY22-2 CFY42-2:



Used to cabin illumination in the hazardous area such as chemical factory, oil refinery, oil and gas plant with explosive gas environment.

Main Specification:

Type	CFY22-2	CFY42-2
Explosion-proof Mark	Exd II C T5	Exd II C T5
Voltage	220V/50Hz,220V/60Hz,110V/60Hz	
Power	2x20W	2X40W
Lamp Holder	G13	
Protection Class	IP54	IP56
Cable Diameter	Dia10-12.5mm	
Weight	6.8kg	14.8kg