

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

MARINE EXPLOSION-PROOF LIGHTS SERIES

Explosion-proof Junction Box, JXD8-4

Main Specification: Current 20A Voltage AC 380V Explosion-Proof Mark Exe II B T6 g...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Explosion-proof Lights Series
Standard	GB
Material	Aluminum
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Explosion-proof Lights Series	Model / SKU	Explosion-proof-Junction-Box-JXD8-4
Standard	GB	Material	Aluminum
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		


 0.052103s

Main Specification:

Current	20A
Voltage	AC 380V
Explosion-Proof Mark	Exe II B T6 gb
Protection Class	IP56
Material	Cast Aluminum Alloy

Explosion Gland

Unarmoured Cable

Screw Thread Specification	Cable Diameter	Protection Class
M20X1.5	Dia.11-14.3	IP66/68
M25X1.5	Dia.13-20.2	IP66/68
M32X1.5	Dia. 19-26.5	IP66/68
M40X1.5	Dia. 25-32.5	IP66/68

Armoured Cable

Screw Thread Specification	Inside Diameter	Outside Diameter	Protection Class
M20X1.5	Dia.11-14.3	Dia.13-20.2	IP66/68
M20X1.5	Dia8-11	Dia. 12-17	IP66/68
M25X1.5	Dia.13-20.2	Dia. 19-26.5	IP66/68
M25X1.5	Dia.12-17	Dia. 17-22	IP66/68
M32X1.5	Dia.19-26.5	Dia. 25-32.5	IP66/68
M32X1.5	Dia.17-22	Dia.23-28	IP66/68
M40X1.5	Dia. 25-32.5	Dia. 31.5-42.3	IP66/68
M40X1.5	Dia. 23-28	Dia.30.37	IP66/68