

CARBON DIOXIDE FIRE FIGHTING SYSTEM

FK-5-1-12 Perfluorohexanone FIRE SUPPRESSION SYSTEM

ISO9001 Supplier

Class Certificate

Export Supply

FK-5-1-12 Perfluorohexanone FIRE SUPPRESSION SYSTEM Cylinder Volume : 10L to 150L Filling Density: Welded cylinders: ≤ 0.95 kg/L ,Seamless gas cylinders: ≤ 1.12 kg/L Design Concentration ...



Key Highlights

Category	Carbon Dioxide Fire Fighting System
Standard	EN
Weight / Size	≤ 0.95 kg/L ,Seamless gas cylinders:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Carbon Dioxide Fire Fighting System	Model / SKU	FK-5-1-12-Perfluorohexanone-FIRE-SUPPRESSION-SYSTEM
Standard	EN	Weight / Size	≤ 0.95 kg/L ,Seamless gas cylinders:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China FK-5-1-12 Perfluorohexanone FIRE SUPPRESSION SYSTEM:

FK-5-1-12 Perfluorohexanone FIRE SUPPRESSION SYSTEM

Cylinder Volume : 10L to 150L

Filling Density: Welded cylinders: ≤ 0.95 kg/L ,Seamless gas cylinders: ≤ 1.12 kg/L

Design Concentration 5.9%



Working Pressure 4.2MPa

Actuation Method:Electric / Pneumatic / Manual

Operating Temperature Range 0 to 50 centigrade

System Composition:Fire extinguishing agent cylinder group, cylinder valve, flexible hose assembly, pneumatic control valve, nozzle, remote release station, alarm box,etc

