

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

SEWAGE PUMP

FX Seires Marine Downdraft Submersible Pump

ISO9001 Supplier

Class Certificate

Export Supply

FX Seires Marine downdraft Submersible Pump are used to transport the freshwater and other purpose the temperature is not higher than 40°C, solid granules is not more than 0.2mm. Impeller with against pine device, Mech...



Key Highlights

| | |
|---------------|---|
| Category | Sewage Pump |
| Standard | EN |
| Material | Impeller with against pine device, Mechanical seal face material USES si... |
| Weight / Size | Main Specification Type Capacity Head Power Current Caliber Weight (m3/h... |
| Certificate | CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



| Technical Specifications | | | |
|--------------------------|--|-------------|---|
| Category | Sewage Pump | Model / SKU | FX-Seires-Marine-Downdraft-Submersible-Pump |
| Standard | EN | Material | Impeller with against pine device, Mechanical seal face material USES silicon carbide - silicon carbide, durable, safe and reliable. |
| Weight / Size | Main Specification Type Capacity Head Power Current Caliber Weight (m3/h) (l/s) (m) (kW) (A) (mm) (kg) FX10-14-0.75 10 2.8 14 0.75 1.8 40 40 FX6-25-1.1 6 1.7 25 1.1 2.73 25 25 FX10-18-1.1 10 2.8 18 1.1 2.73 40 25 FX15-14-1.1 15 4.2 14 1.1 2.73 40 25 FX25-9- 1.1 25 6.9 9 1.1 2.73 50 25 FX40- 6-1.1 40 11.1 6 1.1 2.73 65 34 FX10-24-1.5 10 2.8 24 1.5 3.87 40 32 FX10-34-2.2 10 2.8 34 2.2 6 40 39 FX25-30-3 25 6.9 30 3 6.5 50 45 FX15-45-4 15 4.2 45 4 8.6 40 49 FX25-32-4 25 6.9 32 4 8.6 50 49 FX25-40-5.5 25 6.9 40 5.5 12 50 64 | Certificate | CCS |
| Warranty | 12 Months unless specified otherwise | Origin | China |

CONTENTS

- China FX Seires Marine Downdraft Submersible Pump:
- Main Specification

China FX Seires Marine Downdraft Submersible Pump:



FX Seires Marine downdraft Submersible Pump are used to transport the freshwater and other purpose the temperature is not higher than 40°C, solid granules is not more than 0.2mm. Impeller with against pine device, Mechanical seal face material USES silicon carbide - silicon carbide, durable, safe and reliable.

Main Specification

| Type | Capacity | | Head (m) | Power (kW) | Current (A) | Caliber (mm) | Weight (kg) |
|--------------|---------------------|-------|-------------|---------------|----------------|-----------------|----------------|
| | (m ³ /h) | (l/s) | | | | | |
| FX10-14-0.75 | 10 | 2.8 | 14 | 0.75 | 1.8 | 40 | 40 |
| FX6-25-1.1 | 6 | 1.7 | 25 | 1.1 | 2.73 | 25 | 25 |
| FX10-18-1.1 | 10 | 2.8 | 18 | 1.1 | 2.73 | 40 | 25 |
| FX15-14-1.1 | 15 | 4.2 | 14 | 1.1 | 2.73 | 40 | 25 |
| FX25-9-1.1 | 25 | 6.9 | 9 | 1.1 | 2.73 | 50 | 25 |
| FX40-6-1.1 | 40 | 11.1 | 6 | 1.1 | 2.73 | 65 | 34 |
| FX10-24-1.5 | 10 | 2.8 | 24 | 1.5 | 3.87 | 40 | 32 |
| FX10-34-2.2 | 10 | 2.8 | 34 | 2.2 | 6 | 40 | 39 |
| FX25-30-3 | 25 | 6.9 | 30 | 3 | 6.5 | 50 | 45 |
| FX15-45-4 | 15 | 4.2 | 45 | 4 | 8.6 | 40 | 49 |
| FX25-32-4 | 25 | 6.9 | 32 | 4 | 8.6 | 50 | 49 |
| FX25-40-5.5 | 25 | 6.9 | 40 | 5.5 | 12 | 50 | 64 |