

**MARINE LEVEL SWITCH**

# FYK-221 Float Control Switch

FYK-221 float control switch can adjust liquid level in barrel, trough or well. It can adjust the level switch in barrel, trough or well automatically. It's easy to operate and install. And it's safe, reliable, envir...

- ISO9001 Supplier
- Class Certificate
- Export Supply



### Key Highlights

<b>Category</b>	Marine Level Switch
<b>Standard</b>	ISO
<b>Material</b>	Rated current 5(2.5A) ~2(1A) Rated voltage 250V~380V Power rating 1KW Wo...
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

<b>Category</b>	Marine Level Switch	<b>Model / SKU</b>	FYK-221-Float-Control-Switch
<b>Standard</b>	ISO	<b>Material</b>	Rated current 5(2.5A) ~2(1A) Rated voltage 250V~380V Power rating 1KW Working temperature -10°C~60°C(Plastic) -10°C~150°C (Stainless Steel) Working air pressure 1 atmosphere Working life ≥50000 Control Range≥0.2M Length 1M, 3M, 4M, 5M,10M (Length can also be custom-made to suit your own requirements.)
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	<b>Warranty</b>	12 Months unless specified otherwise
<b>Origin</b>	China		

<b>CONTENTS</b>	<ul style="list-style-type: none"> <li>■ China FYK-221 Float Control Switch:</li> <li>■ Specification:</li> </ul>
-----------------	---

## China FYK-221 Float Control Switch:

FYK-221 float control switch can adjust liquid level in barrel, trough or well.

It can adjust the level switch in barrel, trough or well automatically. It's easy to operate and install. And it's safe, reliable, environmental, non – poison and recuperable. This cable float switch has an effect on resist sewage. It is widely used in the pool in household, factories and mines, used in the pool of oil, acid and alkali and used in barrel, trough and jar.

## Specification:

Rated current	5(2.5A) ~2(1A)
Rated voltage	250V~380V
Power rating	1KW
Working temperature	-10°C~60°C(Plastic)
	-10°C~150°C(Stainless Steel)
Working air pressure	1 atmosphere
Working life	≥50000 Control Range≥0.2M
Length	1M, 3M, 4M, 5M,10M
	(Length can also be custom-made to suit your own requirements.)