

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

OTHER FIRE-FIGHTING EQUIPMENT

Fire Approach Suit Firefighting heat insulation suit

Fire Approach Suit Firefighting heat insulation suit Made by jacket, pants, face shield, mitten and shoes covers Materials&Characteristics: Aluminized Aramid fabrics , heat insulate layer and comfortable I...

ISO9001 Supplier

Class Certificate


Export Supply



Key Highlights

Category	Other Fire-Fighting Equipment
Standard	CB
Material	Fire Approach Suit Firefighting heat insulation suit Made by jacket, pan...
Weight / Size	2 units/carton Size of carton:46x42x33cm N.W./G.W.:9kg/10kgs/carton 90% ...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
Category	Other Fire-Fighting Equipment	Model / SKU	Fire-Approach-Suit-Firefighting-heat-insulation-suit
Standard	CB	Material	Fire Approach Suit Firefighting heat insulation suit Made by jacket, pants, face shield, mitten and shoes covers Materials&Characteristics:
Weight / Size	2 units/carton Size of carton:46x42x33cm N.W./G.W.:9kg/10kgs/carton 90% radiant heat resistant. One hour in the situation of 300 centigrade for 30 minutes in the situation of 500 centigrade, 2 minutes in the situation of 800 centigrade and 1.75 meters to the fire, putting out a fire in the situation of 1000 centigrade in short time. Combust resistance:	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

China Fire Approach Suit Firefighting heat insulation suit:

Fire Approach Suit Firefighting heat insulation suit Made by jacket, pants, face shield, mitten and shoes covers
Materials&Characteristics:

Aluminized Aramid fabrics , heat insulate layer and comfortable layer

Two types:

- 1.Jacket and pants SCBA bag on the back or outside
- 2.Coverall SCBA bag on the back or outside

Feature:

Advanced fireproof, radiant heat resistant, wearable and folded

Packing: 2 units/carton


Size of carton:46x42x33cm

N.W./G.W.:9kg/10kgs/carton

90% radiant heat resistant.

One hour in the situation of 300 centigrade for 30 minutes in the situation of 500 centigrade, 2 minutes in the situation of 800 centigrade and 1.75 meters to the fire, putting out a fire in the situation of 1000 centigrade in short time.

Combust resistance: damaged length equal or less than 10cm, continued burning time equal or less than 2 seconds, no fusing and weeping.



Stripping strength:equal or greater than 9N/30mm

Tearing strength:equal or greater than 450N, fracture strength:equal or greater than 650N

Waterproof:static hydraulic pressure equal or greater than 17KPa

Hard enclosure high temperature protection:without change 5 minutes 260 centigrade.