

# Jinbo Marine

Marine & Offshore Equipment Datasheet


**PRODUCT DATASHEET**

**GAS FITTING**

## Flanged Breather Valve

Main Specification Material Aluminum alloy Nominal Pressure 0.2Mpa Operating medium Gasoline...

- ISO9001 Supplier
- Class Certificate
- Export Supply

	<div style="background-color: #1a3d4d; color: white; padding: 5px;"><b>Key Highlights</b></div> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;"><b>Category</b></td> <td>Gas Fitting</td> </tr> <tr> <td><b>Standard</b></td> <td>EN</td> </tr> <tr> <td><b>Material</b></td> <td>Main Specification Material Aluminum alloy Nominal Pressure 0.2Mpa Opera...</td> </tr> <tr> <td><b>Certificate</b></td> <td>ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS</td> </tr> </table> <p style="font-size: small; margin-top: 10px;">We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.</p>	<b>Category</b>	Gas Fitting	<b>Standard</b>	EN	<b>Material</b>	Main Specification Material Aluminum alloy Nominal Pressure 0.2Mpa Opera...	<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
<b>Category</b>	Gas Fitting								
<b>Standard</b>	EN								
<b>Material</b>	Main Specification Material Aluminum alloy Nominal Pressure 0.2Mpa Opera...								
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS								

Technical Specifications			
<b>Category</b>	Gas Fitting	<b>Model / SKU</b>	Flanged-Breather-Valve
<b>Standard</b>	EN	<b>Material</b>	Main Specification Material Aluminum alloy Nominal Pressure 0.2Mpa Operating medium Gasoline、diedel oil、 coal oil Operating environment -30°C ~ 55°C Threaded joint BSOT1"、 1 1/4"、 1 1/2、 2M32*2
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	<b>Warranty</b>	12 Months unless specified otherwise
<b>Origin</b>	China		





## Main Specification

Material	Aluminum alloy	Nominal Pressure	0.2Mpa
Operating medium	Gasoline、diesel oil、coal oil	Operating environment	-30°C ~ 55°C
Threaded joint	BSOT1"、 1 1/4"、 1 1/2"、 2M32*2		