

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

## MARINE FLUORESCENT LIGHTS

# Fluorescent Pendant Light JCY22-2

Used to illumination of water dripping, water spattering, water coagulating place in ships such as oven cabin, dry cabin tunnel, pipeline and weather deck, environment temperature is -20°C~+55°C.

ISO9001 Supplier

Class Certificate

Export Supply



### Key Highlights

Category	Marine Fluorescent Lights
Standard	EN
Material	Steel Plate, PC Material and Seal Structure
Weight / Size	Voltage 110V/60Hz, 220V/50Hz, 220V/60Hz Power Factor >0.85 Lamp Holder G...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



0.042985s

Technical Specifications			
<b>Category</b>	Marine Fluorescent Lights	<b>Model / SKU</b>	Fluorescent-Pendant-Light-JCY22-2
<b>Standard</b>	EN	<b>Material</b>	Steel Plate, PC Material and Seal Structure
<b>Weight / Size</b>	Voltage 110V/60Hz, 220V/50Hz, 220V/60Hz Power Factor >0.85 Lamp Holder G13 Cable Diameter Dia14mm-16mm Protection Class IP56 Type JCY22-2 JCY22-2E JCY22-2EF JCY32-2 JCY32-2E JCY32-2EF JCY42-2 JCY42-2E JCY42-2EF Power 2X20W 2X20W 2X20W 2X30W 2X30W 2X30W 2X40W 2X40W 2X40W Weight 7.2kg 7.2kg 7.2kg 9kg 9kg 9kg 11kg 11kg 11kg Ballast	<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
<b>Warranty</b>	12 Months unless specified otherwise	<b>Origin</b>	China

<b>CONTENTS</b>	<ul style="list-style-type: none"> <li>■ China Fluorescent Pendant Light JCY22-2:</li> <li>■ Main Specification:</li> </ul>	<ul style="list-style-type: none"> <li>■ Standards:</li> <li>■ Ballast</li> </ul>
-----------------	---	---

## China Fluorescent Pendant Light JCY22-2:



Used to illumination of water dripping, water spattering, water coagulating place in ships such as oven cabin, dry cabin tunnel, pipeline and weather deck, environment temperature is -20°C~+55°C.

### Standards:

Confirm to IEC600092-306-2009 and GRADE ENTRY NORMS FOR STEEL SHIPS.

Our product approved by the CCS(China Classification Society)



## Main Specification:

Voltage	110V/60Hz, 220V/50Hz, 220V/60Hz
Power Factor	>0.85
Lamp Holder	G13
Cable Diameter	Dia14mm-16mm
Protection Class	IP56

Type	JCY22-2	JCY22-2E	JCY22-2EF	JCY32-2	JCY32-2E	JCY32-2EF	JCY42-2	JCY42-2E	JCY42-2EF
Power	2X20W	2X20W	2X20W	2X30W	2X30W	2X30W	2X40W	2X40W	2X40W
Weight	7.2kg	7.2kg	7.2kg	9kg	9kg	9kg	11kg	11kg	11kg

## Ballast

