MARINE FLUORESCENT LIGHTS

Fluorescent Pendant Light JCY22-2

Used to illumination of water dripping, water spattering, water coagulating place in ships such as oven cabin, dry cabin tunnel, pipeline and weather deck, environment temperature is -20°C~+55°C.

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Fluorescent Lights
Standard	EN
Material	Steel Plate, PC Material and Seal Structure
Weight / Size	Voltage 110V/60Hz, 220V/50Hz, 220V/60Hz Power Factor >0.85 Lamp Holder G...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Fluorescent Lights	**Model / SKU**	Fluorescent-Pendant-Light-JCY22-2
Standard	EN	**Material**	Steel Plate, PC Material and Seal Structure
Weight / Size	Voltage 110V/60Hz, 220V/50Hz, 220V/60Hz Power Factor >0.85 Lamp Holder G13 Cable Diameter Dia14mm-16mm Protection Class IP56 Type JCY22-2 JCY22-2E JCY22-2EF JCY32-2 JCY32-2E JCY32-2EF JCY42-2 JCY42-2E JCY42-2EF Power 2X20W 2X20W 2X20W 2X30W 2X30W 2X30W 2X40W 2X40W 2X40W Weight 7.2kg 7.2kg 7.2kg 9kg 9kg 9kg 11kg 11kg 11kg Ballast	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

CONTENTS

- China Fluorescent Pendant Light JCY22-2:
- Main Specification:
- Standards:
- Ballast

China Fluorescent Pendant Light JCY22-2:



Used to illumination of water dripping, water spattering, water coagulating place in ships such as oven cabin, dry cabin tunnel, pipeline and weather deck, environment temperature is -20°C~+55°C.

Standards:

Confirm to IEC600092-306-2009 and GRADE ENTRY NORMS FOR STEEL SHIPS.

Our product approved by the CCS(China Classification Society)

Main Specification:

Voltage	110V/60Hz, 220V/50Hz, 220V/60Hz
Power Factor	>0.85
Lamp Holder	G13
Cable Diameter	Dia14mm-16mm
Protection Class	IP56

Type	JCY22-2	JCY22-2E	JCY22-2EF	JCY32-2	JCY32-2E	JCY32-2EF	JCY42-2	JCY42-2E	JCY42-2EF
Power	2X20W	2X20W	2X20W	2X30W	2X30W	2X30W	2X40W	2X40W	2X40W
Weight	7.2kg	7.2kg	7.2kg	9kg	9kg	9kg	11kg	11kg	11kg

Ballast



