


**MARINE FLUORESCENT LIGHTS**

# Fluorescent Pendant Light JCY28-1

Used to illumination of water dripping, water spattering, water coagulating place in ships, such as oven cabin, tunnel pipeline and weather deck etc. The working enviroment temperature is -20°C~+55°C. Main S...

- ISO9001 Supplier
- Class Certificate
- Export Supply

	<p><b>Key Highlights</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="background-color: #1a3d4d; color: white; padding: 5px;"><b>Category</b></td> <td style="padding: 5px;">Marine Fluorescent Lights</td> </tr> <tr> <td style="background-color: #1a3d4d; color: white; padding: 5px;"><b>Standard</b></td> <td style="padding: 5px;">EN</td> </tr> <tr> <td style="background-color: #1a3d4d; color: white; padding: 5px;"><b>Material</b></td> <td style="padding: 5px;">Steel Plate, PC Material and Seal Structure</td> </tr> <tr> <td style="background-color: #1a3d4d; color: white; padding: 5px;"><b>Weight / Size</b></td> <td style="padding: 5px;">Type JCY28-1 JCY28-2 JCY28-1B JCY28-2B Voltage 110V/60Hz, 220V/50Hz, 220...</td> </tr> <tr> <td style="background-color: #1a3d4d; color: white; padding: 5px;"><b>Certificate</b></td> <td style="padding: 5px;">ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS</td> </tr> </table> <p style="font-size: small; margin-top: 10px;">We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.</p>	<b>Category</b>	Marine Fluorescent Lights	<b>Standard</b>	EN	<b>Material</b>	Steel Plate, PC Material and Seal Structure	<b>Weight / Size</b>	Type JCY28-1 JCY28-2 JCY28-1B JCY28-2B Voltage 110V/60Hz, 220V/50Hz, 220...	<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
<b>Category</b>	Marine Fluorescent Lights										
<b>Standard</b>	EN										
<b>Material</b>	Steel Plate, PC Material and Seal Structure										
<b>Weight / Size</b>	Type JCY28-1 JCY28-2 JCY28-1B JCY28-2B Voltage 110V/60Hz, 220V/50Hz, 220...										
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS										

Technical Specifications			
<b>Category</b>	Marine Fluorescent Lights	<b>Model / SKU</b>	Fluorescent-Pendant-Light-JCY28-1
<b>Standard</b>	EN	<b>Material</b>	Steel Plate, PC Material and Seal Structure
<b>Weight / Size</b>	Type JCY28-1 JCY28-2 JCY28-1B JCY28-2B Voltage 110V/60Hz, 220V/50Hz, 220V/60Hz Power Factor >0.85 Lamp Holder G13 Cable Diameter Dia8mm-16mm Protection Class IP67 Power 1x20W 1x20W 1X20W 2X20W Weight 7.2kg 7.2kg 7.2kg 7.2kg	<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
<b>Warranty</b>	12 Months unless specified otherwise	<b>Origin</b>	China



## China Fluorescent Pendant Light JCY28-1:



Used to illumination of water dripping, water spattering, water coagulating place in ships, such as oven cabin, tunnel pipeline and weather deck etc. The working environment temperature is  $-20^{\circ}\text{C}\sim+55^{\circ}\text{C}$ .

### Main Specification:

Type	JCY28-1	JCY28-2	JCY28-1B	JCY28-2B
Voltage	110V/60Hz, 220V/50Hz, 220V/60Hz			
Power Factor	>0.85			
Lamp Holder	G13			
Cable Diameter	Dia8mm-16mm			
Protection Class	IP67			
Power	1x20W	1x20W	1X20W	2X20W
Weight	7.2kg	7.2kg	7.2kg	7.2kg