

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

OIL HOSE

Fuel Discharge Hose

Used in all kinds of oil pump, the reinforcement is tire cord layer T: Black Nitrile Rubber R: Braided Wire Layer Working Temperature: -30°C to +80°C Safety Factor: 1:3 Specification...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Oil Hose
Standard	EN
Material	NR, SBR, BR
Weight / Size	1:3 Specification ID OD Length Bend radius WP Weight in mm in mm ft m in...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Oil Hose	Model / SKU	Fuel-Discharge-Hose
Standard	EN	Material	NR, SBR, BR
Weight / Size	1:3 Specification ID OD Length Bend radius WP Weight in mm in mm ft m in mm Psi Kg/cm ² Kg/m 2 50.8 2.709 68.8 66 20 14 350 150 10 2.69 2 1/2 63.5 3.209 81.5 66 20 16 400 150 10 3.22 3 76.2 3.803 96.6 66 20 18 450 150 10 4.19 4 101.6 5.031 127.8 66 20 24 600 150 10 7.33 5 127 6.031 153.2 66 20 30 750 150 10 8.89 6 152.4 7.142 181.4 66 20 34 850 150 10 13.76 8 203.2 9.409 239 66 20 44 1100 150 10 21.17 10 254 12.063 306.4 33 10 54 1350 150 10 41.34 12 304.8 14.126 358.8 33 10 64 1600 150 10 50	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	■ China Fuel Discharge Hose:	■ Specification
----------	------------------------------	-----------------

China Fuel Discharge Hose:

Used in all kinds of oil pump, the reinforcement is tire cord layer

T: Black Nitrile Rubber

R: Braided Wire Layer

Working Temperature: -30°C to +80°C

Safety Factor: 1:3

Specification

ID		OD		Length		Bend radius		WP		Weight
in	mm	in	mm	ft	m	in	mm	Psi	Kg/cm ²	Kg/m
2	50.8	2.709	68.8	66	20	14	350	150	10	2.69
2 1/2	63.5	3.209	81.5	66	20	16	400	150	10	3.22
3	76.2	3.803	96.6	66	20	18	450	150	10	4.19
4	101.6	5.031	127.8	66	20	24	600	150	10	7.33

5	127	6.031	153.2	66	20	30	750	150	10	8.89
6	152.4	7.142	181.4	66	20	34	850	150	10	13.76
8	203.2	9.409	239	66	20	44	1100	150	10	21.17
10	254	12.063	306.4	33	10	54	1350	150	10	41.34
12	304.8	14.126	358.8	33	10	64	1600	150	10	50