

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

## CONNECTORS

# G2130 Bow Shackle

The bow shackle is common produce used in the offshore industry, this shackle can be used in temporary and permanent in the mooring system, finish is hot dip galvanized.

ISO9001 Supplier

Class Certificate

Export Supply



### Key Highlights

<b>Category</b>	Connectors
<b>Standard</b>	EN
<b>Weight / Size</b>	Nominal Size Working Load Dimensions Weight (in.) (tons) A B C D E F H L...
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
<b>Category</b>	Connectors	<b>Model / SKU</b>	G2130-Bow-Shackle
<b>Standard</b>	EN	<b>Weight / Size</b>	Nominal Size Working Load Dimensions Weight (in.) (tons) A B C D E F H L N (lbs.) 3/16 1/3 0.38 0.25 0.88 0.19 0.6 0.56 1.47 0.98 0.19 0.06 1/4 1/2 0.47 0.31 1.13 0.25 0.78 0.61 1.84 1.28 0.25 0.11 5/16 3/4 0.53 0.38 1.22 0.31 0.84 0.75 2.09 1.47 0.31 0.22 3/8 1 0.66 0.44 1.44 0.38 1.03 0.91 2.49 1.78 0.38 0.33 7/16 1 1/2 0.75 0.5 1.69 0.44 1.16 1.06 2.91 2.03 0.44 0.49 1/2 2 0.81 0.64 1.88 0.5 1.31 1.19 3.28 2.31 0.5 0.79 5/8 3 1/4 1.06 0.77 2.38 0.63 1.69 1.5 4.19 2.94 0.69 1.68 3/4 4 3/4 1.25 0.89 2.81 0.75 2 1.81 4.97 3.5 0.81 2.72 7/8 6 1/2 1.44 1.02 3.31 0.88 2.28 2.09 5.83 4.03 0.97 3.95   8 1/2 1.69 1.15 3.75 1 2.69 2.38 6.56 4.69 1.06 5.66   1/8 9 1/2 1.81 1.25 4.25 1.13 2.91 2.69 7.47 5.16 1.25 8.27   1/4 12 2.03 1.4 4.69 1.29 3.25 3 8.25 5.75 1.38 11.71   3/8 13 1/1 2.25 1.53 5.25 1.42 3.63 3.31 9.16 6.38 1.5 15.83   1/2 17 2.38 1.66 5.75 1.53 3.88 3.63 10 6.88 1.62 19   3/4 25 2.88 2.04 7 1.84 5 4.19 12.34 8.8 2.25 33.91 2 35 3.25 2.3 7.75 2.08 5.75 4.81 13.68 10.15 2.4 52.25 2.5 55 4.13 2.8 10.5 2.71 7.25 5.69 17.9 12.75 3.13 98.25 3 85 5 3.3 13 3.12 7.88 6.5 21.5 14.62 3.62 154 3.5 120 5.25 3.76 14.63 3.62 9 8 24.88 17.02 4.38 265 4 150 5.5 4.26 14.5 4 10 9 25.68 18 4.56 338
<b>Surface</b>	hot dip galvanized	<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
<b>Warranty</b>	12 Months unless specified otherwise	<b>Origin</b>	China

<b>CONTENTS</b>	<ul style="list-style-type: none"> <li>■ China G2130 Bow Shackle:</li> <li>■ Main Specification:</li> </ul>
-----------------	---



## China G2130 Bow Shackle:



The bow shackle is common produce used in the offshore industry, this shackle can be used in temporary and permanent in the mooring system, finish is hot dip galvanized.

## Main Specification:

Nominal Size	Working Load	Dimensions									Weight
(in.)	(tons)	A	B	C	D	E	F	H	L	N	(lbs.)
3/16	1/3	0.38	0.25	0.88	0.19	0.6	0.56	1.47	0.98	0.19	0.06
1/4	1/2	0.47	0.31	1.13	0.25	0.78	0.61	1.84	1.28	0.25	0.11
5/16	3/4	0.53	0.38	1.22	0.31	0.84	0.75	2.09	1.47	0.31	0.22
3/8	1	0.66	0.44	1.44	0.38	1.03	0.91	2.49	1.78	0.38	0.33
7/16	1 1/2	0.75	0.5	1.69	0.44	1.16	1.06	2.91	2.03	0.44	0.49
1/2	2	0.81	0.64	1.88	0.5	1.31	1.19	3.28	2.31	0.5	0.79
5/8	3 1/4	1.06	0.77	2.38	0.63	1.69	1.5	4.19	2.94	0.69	1.68
3/4	4 3/4	1.25	0.89	2.81	0.75	2	1.81	4.97	3.5	0.81	2.72
7/8	6 1/2	1.44	1.02	3.31	0.88	2.28	2.09	5.83	4.03	0.97	3.95
1	8 1/2	1.69	1.15	3.75	1	2.69	2.38	6.56	4.69	1.06	5.66
1 1/8	9 1/2	1.81	1.25	4.25	1.13	2.91	2.69	7.47	5.16	1.25	8.27
1 1/4	12	2.03	1.4	4.69	1.29	3.25	3	8.25	5.75	1.38	11.71
1 3/8	13 1/1	2.25	1.53	5.25	1.42	3.63	3.31	9.16	6.38	1.5	15.83
1 1/2	17	2.38	1.66	5.75	1.53	3.88	3.63	10	6.88	1.62	19
1 3/4	25	2.88	2.04	7	1.84	5	4.19	12.34	8.8	2.25	33.91
2	35	3.25	2.3	7.75	2.08	5.75	4.81	13.68	10.15	2.4	52.25
2.5	55	4.13	2.8	10.5	2.71	7.25	5.69	17.9	12.75	3.13	98.25
3	85	5	3.3	13	3.12	7.88	6.5	21.5	14.62	3.62	154

3.5	120	5.25	3.76	14.63	3.62	9	8	24.88	17.02	4.38	265
4	150	5.5	4.26	14.5	4	10	9	25.68	18	4.56	338

