

# Jinbo Marine

Marine &amp; Offshore Equipment Datasheet

PRODUCT DATASHEET

## NAVIGATION BUOY

## HD300-L1 LED Lantern

Specifications Light Base Alumnum Characteristic&nbsp; 256 program&nbsp; Optical sensitivity ...

ISO9001 Supplier

Class Certificate

Export Supply



### Key Highlights

<b>Category</b>	Navigation Buoy
<b>Standard</b>	EN
<b>Weight / Size</b>	Specifications Light Base Alumnum Characteristic 256 program Optical ...
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

<b>Category</b>	Navigation Buoy	<b>Model / SKU</b>	HD300-L1-LED-Lantern
<b>Standard</b>	EN	<b>Weight / Size</b>	Specifications Light Base Alumnum Characteristic 256 program Optical sensitivity 300LX Source LED Voltage 10-18V Installation 3-Φ13/200mm Weight 12kg HD100-S1 LED Lantern Voltage DC12V Power 2W Source LED Navigation Range >2nm Characteristic 256 program Color Red, Yellow, Green, White Optical sensitivity 300LX Working Environment Outdoor, Waterproof Protection IP65 Working Temperature -25-65°C Installation 4-Φ20/Φ195mm
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	<b>Warranty</b>	12 Months unless specified otherwise
<b>Origin</b>	China		



0.066637s

## Specifications

Light Base	Aluminium
Characteristic	256 program
Optical sensitivity	300LX
Source	LED
Voltage	10-18V
Installation	3- $\Phi$ 13/200mm
Weight	12kg
HD100-S1 LED Lantern	
Voltage	DC12V
Power	2W
Source	LED Navigation
Range	>2nm
Characteristic	256 program
Color	Red, Yellow, Green, White
Optical sensitivity	300LX
Working Environment	Outdoor, Waterproof
Protection	IP65
Working Temperature	-25-65°C
Installation	4- $\Phi$ 20/ $\Phi$ 195mm