

LIFEBOAT AND RESCUE BOAT ACCESSORIES

HDWD5-24D20L Marine Battery Charger Power Supply

ISO9001 Supplier

Class Certificate

Export Supply

Description: HDWD5-24D20L Marine Battery Charger Power Supplyseries of products meet the specifications and requirements for the use of electrical equipment related to international and domestic navigation vessel...



Key Highlights

Category	Lifeboat And Rescue Boat Accessories
Standard	DIN
Weight / Size	32V / 1A) Indication and adjustment Input instructions, work instruction...
Certificate	CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Lifeboat And Rescue Boat Accessories	Model / SKU	HDWD5-24D20L-Marine-Battery-Charger-Power-Supply
Standard	DIN	Weight / Size	32V / 1A) Indication and adjustment Input instructions, work instructions, fault instructions, current regulation Working environment Operating temperature -15°C~+55°C Storage temperature -25°C~+85°C Relative humidity 0~95% (Non-condensing) Atmospheric pressure 70kPa~106kPa Cooling method Air-cooled Standard range Safety IEC61000-4-2、 IEC61000-4-3、 IEC61000-4-4、 IEC61000-4-5、 IEC61000-4-6、 IEC60092-101、 IEC60068-2-11 Conduction, radiation CISPR16、 EN55022 Certification CCS Type Approval Others Size(WxDxH)mm 42x124x152 Weight 0.7kg Installation method Bottom plate installation
Certificate	CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS
 Description:

 Technical data:

Description:

HDWD5-24D20L Marine Battery Charger Power Supplyseries of products meet the specifications and requirements for the use of electrical equipment related to international and domestic navigation vessels.

1. Comprehensive protection functions, including input under-voltage, over-voltage protection, output over-voltage protection, output short-circuit protection, over-temperature protection, etc.
2. In order to meet the special needs of customers, it can be expanded into a charging power supply and can be expanded into a 12V output mode.
3. High power density design, high voltage stabilization accuracy, more reliable performance, efficiency up to 90%.
4. Use bottom plate installation or optional standard TH35 rail installation.

Technical data:



Specifications (Output current)		5A
Input	Rated voltage	24VDC
	Input range	Rated voltage±20%
	Input frequency	45~65HZ
	Efficiency	≥88%
	Maximum current	Single-phase 220 < 8.5A
Output	voltage	24VDC±0.1V(Can be adjusted according to customer requirements and battery specifications)
	Average floating charge conversion current	±1%
	Regulation accuracy	VPP≤200mV
Output	Alarm and protection functions	Input under voltage protection, input over voltage protection, output under voltage warning, output over voltage protection, output short circuit protection, output over current protection, power supply over temperature protection
	Standard functions	Public warning, fault passive dry contact port (contact limit specification: 32V / 1A)
	Indication and adjustment	Input instructions, work instructions, fault instructions, current regulation
Working environment	Operating temperature	-15°C~+55°C
	Storage temperature	-25°C~+85°C
	Relative humidity	0~95% (Non-condensing)
	Atmospheric pressure	70kPa~106kPa
	Cooling method	Air-cooled
Standard range	Safety	IEC61000-4-2、 IEC61000-4-3、 IEC61000-4-4、 IEC61000-4-5、 IEC61000-4-6、 IEC60092-101、 IEC60068-2-11
	Conduction, radiation	CISPR16、 EN55022
	Certification	CCS Type Approval
Others	Size(WxDxH)mm	42x124x152
	Weight	0.7kg
	Installation method	Bottom plate installation

