

HAMMER UNION

HIGH, MEDIUM AND LOW PRESSURE UNIONS FIG200

ISO9001 Supplier

Class Certificate

Export Supply

HIGH, MEDIUM AND LOW PRESSURE UNIONS With the compact structure;the unions are widely used for low pressure kill line and also can be used for usage occasions of air, water, oil or gases within the scope ...



Key Highlights

Category	Hammer Union
Standard	EN
Weight / Size	Specifications and Reference Sizes of Union Type 200:2000PSI NSCWP, test...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Hammer Union	Model / SKU	HIGH-MEDIUM-AND-LOW-PRESSURE-UNIONS-FIG200
Standard	EN	Weight / Size	Specifications and Reference Sizes of Union Type 200:2000PSI NSCWP, test pressure:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

■ HIGH, MEDIUM AND LOW PRESSURE UNIONS

■ Specifications and Reference Sizes of Union

HIGH, MEDIUM AND LOW PRESSURE UNIONS



With the compact structure, the unions are widely used for low pressure kill line and also can be used for usage occasions of air, water, oil or gases within the scope of medium pressure. The butt-welded Sch.40 is used for usable model.

Specifications and Reference Sizes of Union

标称管道尺寸 Nominal pipe size		总长 Total length		螺母半径 Nut radius		材料 Material		重量 Weight	
in	mm	in	mm	in	mm	螺母 Nut	零件 Part	lb	kg
1	25.4	2 ³ / ₁₆	68.3	1 ³ / ₁₆	49.2	SC/SF	CDR/SF	1.75	0.8
1 ¹ / ₄	31.7	2 ¹ / ₈	73.0	2 ¹ / ₈	60.3	SF	SF	2.37	1.1
1 ¹ / ₂	38.1	2 ¹ / ₈	73.0	2 ¹ / ₈	60.3	SF	SF	2.37	1.1
2	50.8	3 ¹ / ₈	84.1	2 ⁹ / ₁₆	73.8	SF	SF	5.25	2.4
2 ¹ / ₂	63.8	4 ¹ / ₈	103.2	3 ¹ / ₁₆	93.7	SF	SF	10.0	4.5
3	76.2	4 ¹ / ₈	111.1	3 ¹ / ₈	98.4	SF	SF	15.25	6.9
4	101.6	4 ¹ / ₈	122.2	5	127.0	SF	SF	20.0	9.1
6	152.4	6 ¹ / ₈	168.3	6 ¹ / ₁₆	163.5	SF	SF	44.5	20.2
		1 ¹ / ₄		1 ¹ / ₄					

Type 200:2000PSI NSCWP, test pressure: 3000PSI, blue nut and grey part.