MARINE HOIST

HSH-A619 Lever Hoist

ISO9001 Supplier

Class Certificate

Export Supply

Two points support,the driving shaft is fixed by cantilever structure,the hand wheel is stamping,more compact and reliable operation. The friction disc and ratchet as replacement parts, more convenient. It on...



Key Highlights

Category	Marine Hoist
Standard	EN
Material	G80 Chain
Weight / Size	Model H0075-A619 H015-A619 H030-A619 H060-A619 H090-A619 Capacity Tons 0...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Hoist	**Model / SKU**	HSH-A619-Lever-Hoist
Standard	EN	**Material**	G80 Chain
Weight / Size	Model H0075-A619 H015-A619 H030-A619 H060-A619 H090-A619 Capacity Tons 0.75 1.5 3 6 9 Load Chain mm 6x18 8x24 10x30 10x30 10x30 Strands of load chain 1 1 1 2 3 Strands of lift mm 1.5 1.5 1.5 1.5 1.5 Load chain distance by rotating the hand wheel one circle mm 19.8 21.3 16.8 8.4 5.6 Effort required to lift rated load N 140 240 320 340 360 Running test load KN 9.2 18.4 36.8 73.5 110.3 Dimensions(mm) A 148 176 195 195 195 B 88 102 109 109 109 C 135 162 211 254 319 D 37 45 50 64 85 Hmin 320 380 480 620 700 L 290 420 420 420 420 K 26 32.5 37 46 50 Extra weight per meters of extra lift 0.8 1.4 2.2 4.3 6.6 Net weight 0.3 11 18.7 30 41.2	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

CONTENTS

- China HSH-A619 Lever Hoist:
- Specification:

China HSH-A619 Lever Hoist:

Two points support,the driving shaft is fixed by cantilever structure,the hand wheel is stamping,more compact and reliable operation.

The friction disc and ratchet as replacement parts, more convenient.

It on Ratchet part,the performance of maintenance-free bearing is close to rolling bearing,better corrosion resistance.

The material of hook is alloy steel,passed heat treatment,it iincludes stamping safety latch.

Optional feature:cast safety latch.

The material of handle seeve is oil resistant rubber. Grade 80 load chain.

Optional feature:Grade 100 load chain.

Grade 80 loade chain is accorded with EN818-7 standard.


The stamping enlarged end ring support 2.5 times of rated load.


Optional feature: cast enlarged end ring and mobile end ring.

Brake seat and driving shaft connected by screw thread.

Specification:

Model	H0075-A619	H015-A619	H030-A619	H060-A619	H090-A619	
Capacity	Tons	0.75	1.5	3	6	9
Load Chain	mm	6x18	8x24	10x30	10x30	10x30
Strands of load chain		1	1	1	2	3
Strands of lift	mm	1.5	1.5	1.5	1.5	1.5
Load chain distance by rotating the hand wheel one circle	mm	19.8	21.3	16.8	8.4	5.6
Effort required to lift rated load	N	140	240	320	340	360
Running test load	KN	9.2	18.4	36.8	73.5	110.3
Dimensions(mm)	A	148	176	195	195	195
	B	88	102	109	109	109
	C	135	162	211	254	319
	D	37	45	50	64	85
	Hmin	320	380	480	620	700
	L	290	420	420	420	420
	K	26	32.5	37	46	50
Extra weight per meters of extra lift		0.8	1.4	2.2	4.3	6.6
Net weight		0.3	11	18.7	30	41.2





0.75t,1.5t,3t *6t* *9t*