

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

FIRE DETECTION AND ALARM SYSTEM

HY-M900K Manual Fire Alarm Button

Color: Red Shell Material: ABS Fire Retardant Cable Gland: 2-PG16 Voltage: DC15V-33V
Current: $\leq 5\mu\text{A}$ Alarm Current: $\leq 30\text{mA}$

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Fire Detection and Alarm System
Standard	EN
Material	Red Shell Material:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Fire Detection and Alarm System	Model / SKU	HY-M900K-Manual-Fire-Alarm-Button
Standard	EN	Material	Red Shell Material:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China HY-M900K Manual Fire Alarm Button:

Color: Red

Shell Material: ABS Fire Retardant

Cable Gland: 2-PG16

Voltage: DC15V-33V

Current: $\leq 5\mu\text{A}$ Alarm Current: $\leq 30\text{mA}$ 

