HAND PUMP

Half Twist-action Hand Pump K Series

ISO9001 Supplier

Class Certificate

Export Supply

Half Twist-action Hand Pump Half twist-action hand pump clean water, gasoline, kerosene, and iron and copper and other non-corrosive liquids, does not apply to fiber or other solid particles of the liquid, pumping...



Key Highlights

Category	Hand Pump
Standard	EN
Material	cast iron
Weight / Size	Main Specification Model Inlet and outlet size weight Double strokes Cap...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Hand Pump	**Model / SKU**	Half-Twist-action-Hand-Pump-K-Series
Standard	EN	**Material**	cast iron
Weight / Size	Main Specification Model Inlet and outlet size weight Double strokes Capacity Head Pieces per case Gross weight kg per min l/min m kg K00 3/8" 3 80 7.5 25 30 117 K0 1/2" 5 65 11.5 25 30 174 K1 3/4" 6 60 17.25 25 25 174 K2 1" 8 55 22.5 25 15 153 K3 1-1/4" 11 50 29 22 10 136 K4 1-1/4" 12 50 43.25 22 8 122 K5 1-1/2" 17 45 53.5 20 6 117 K7 2" 30 40 90 15 3 116 D40 1-1/2" 13.5 40 50 15 10 155	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

CONTENTS

- Half Twist-action Hand Pump
- Main Specification

Half Twist-action Hand Pump

Half twist-action hand pump clean water, gasoline, kerosene, and iron and copper and other non-corrosive liquids, does not apply to fiber or other solid particles of the liquid, pumping the liquid below the temperature of 60℃.

Its performance range: flow rate 15-105 l/min, maximum lift of 26 meters. CYL hand pump compact structure, beautiful style and generous, easy to use and reliable.

Main Specification

Model	Inlet and outlet size	weight	Double strokes	Capacity	Head	Pieces per case	Gross weight
kg	per min	l/min	m	kg			
K00	3/8"	3	80	7.5	25	30	117
K0	1/2"	5	65	11.5	25	30	174
K1	3/4"	6	60	17.25	25	25	174
K2	1"	8	55	22.5	25	15	153
K3	1-1/4"	11	50	29	22	10	136
K4	1-1/4"	12	50	43.25	22	8	122
K5	1-1/2"	17	45	53.5	20	6	117
K7	2"	30	40	90	15	3	116
D40	1-1/2"	13.5	40	50	15	10	155