

# Jinbo Marine

Marine &amp; Offshore Equipment Datasheet

PRODUCT DATASHEET

## HAMMER UNION

# Hammer Union 3" Figure 1002 Thread

Type 1002 union rated pressure 10000 PSI NSCWP, test pressure 15000 PSI, recommended for cementing, fracturing, acidizing and block and kill line. It also used in high pressure system, including vehicle system and als...

ISO9001 Supplier

Class Certificate

Export Supply



### Key Highlights

Category	Hammer Union
Standard	DIN
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

Category	Hammer Union	Model / SKU	Hammer-Union-3-Figure-1002-Thread
Standard	DIN	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

### China Hammer Union 3" Figure 1002 Thread:

Type 1002 union rated pressure 10000 PSI NSCWP, test pressure 15000 PSI, recommended for cementing, fracturing, acidizing and block and kill line. It also used in high pressure system, including vehicle system and also be used as a pressure seal union, using the butt welding Sch. 160 or XXH. Equipped with elastic nitrile rubber sealing ring.

