

**HAMMER UNION**

# Hammer Union 3" Figure 1003 Thread

Type 1003 union rated pressure 10000 PSI NSCWP (7500 psi NSCWP, in 4, 5 in), recommended for applied to air, water, gas, oil, mud or air use occasion. Union has a spherical seat, which can provide the off-center ...

- ISO9001 Supplier
- Class Certificate
- Export Supply



### Key Highlights

<b>Category</b>	Hammer Union
<b>Standard</b>	EN
<b>Material</b>	In addition to the steel on steel cooperation, nitrile rubber type O - r...
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

<b>Category</b>	Hammer Union	<b>Model / SKU</b>	Hammer-Union-3-Figure-1003-Thread
<b>Standard</b>	EN	<b>Material</b>	In addition to the steel on steel cooperation, nitrile rubber type O - ring to ensure the position in any deflection connection tightness.
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	<b>Warranty</b>	12 Months unless specified otherwise
<b>Origin</b>	China		

### China Hammer Union 3" Figure 1003 Thread:

Type 1003 union rated pressure 10000 PSI NSCWP (7500 psi NSCWP, in 4, 5 in), recommended for applied to air, water, gas, oil, mud or air use occasion. Union has a spherical seat, which can provide the off-center 71/2 degree deflection or Angle adjustment, the total deflection capacity is 15 degrees. In addition to the steel on steel cooperation, nitrile rubber type O - ring to ensure the position in any deflection connection tightness.

