MANUAL OPERATED FIRE MONITOR

Hand Operated Monitor PS30-50B

ISO9001 Supplier

Class Certificate

Export Supply

Type: PS30-50B Flow Range: 30-40-50 L/S Adjustable Working Pressure: 10 bar Max Reach @ Max Flow: 65m Range of motion: -45°~+90°Vert , 360°Rot Max fog angle ：120° Material (body)：Aluminum Material (Gear)：bronze M...



Key Highlights

Category	Manual Operated Fire Monitor
Standard	EN
Material	-45°~+90°Vert , 360°Rot Max fog angle ：120° Material (body)：Aluminum Mat...
Weight / Size	-45°~+90°Vert , 360°Rot Max fog angle ：120° Material (body)：Aluminum Mat...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Manual Operated Fire Monitor	**Model / SKU**	Hand-Operated-Monitor-PS30-50B
Standard	EN	**Material**	-45°~+90°Vert , 360°Rot Max fog angle ：120° Material (body)：Aluminum Material (Gear)：bronze Material (nozzle)：Aluminum Material (handwheel) ： chromate cast iron Pump requirement for minimum performance：30L/S@ 8 bar Pipe dimensions for installation:
Weight / Size	-45°~+90°Vert , 360°Rot Max fog angle ：120° Material (body)：Aluminum Material (Gear)：bronze Material (nozzle)：Aluminum Material (handwheel) ： chromate cast iron Pump requirement for minimum performance：30L/S@ 8 bar Pipe dimensions for installation:	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

China Hand Operated Monitor PS30-50B:

Type: PS30-50B
Flow Range: 30-40-50 L/S Adjustable
Working Pressure: 10 bar
Max Reach @ Max Flow: 65m
Range of motion: -45°~+90°Vert , 360°Rot
Max fog angle ：120°
Material (body)：Aluminum
Material (Gear)：bronze
Material (nozzle)：Aluminum
Material (handwheel) ： chromate cast iron
Pump requirement for minimum performance：30L/S@ 8 bar
Pipe dimensions for installation: 4 Inch
Monitor Inlet: DN100 flange
Monitor Outlet：2.5 inch (65mm)
Paint: Fire Red
Weight: 16KG