

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

MARINE WINDLASS

Hydraulic Double Gypsy Windlass

We can design the windlass for anchor chain from 12.5~114mm. The windlass can be driven by the electric motor, hydraulic pump station. Speed:9~20m/min Chain Diameter(mm) ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Windlass
Standard	DIN
Material	Cast Steel
Certificate	CCS, BV, ABS, DNV/GL, LR, NK, IRS, RMRS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Windlass	Model / SKU	Hydraulic-Double-Gypsy-Windlass
Standard	DIN	Material	Cast Steel
Certificate	CCS, BV, ABS, DNV/GL, LR, NK, IRS, RMRS	Warranty	12 Months unless specified otherwise
Origin	China		

China Hydraulic Double Gypsy Windlass:

We can design the windlass for anchor chain from 12.5~114mm. The windlass can be driven by the electric motor, hydraulic pump station.

Speed:9~20m/min

Chain Diameter(mm)	Rated Load(KN AM2)	Overload (KN AM2)	Holding Load(KN AM2)	Power (KW)
12.5	6.6	9.9	41.4	4
14	8.3	12.5	52.2	4
16	10.9	16.4	67.5	5.5

17.5	13	19.5	80.5	5.5
19	15.3	23	94.9	5.5
20.5	17.9	26.9	109.8	7.5
22	20.6	30.9	126	7.5
24	24.5	36.8	145	11
26	28.7	43	175	11
28	33.3	49.9	202	15
30	38.3	57.5	231	15
32	43.5	65.3	262	18.5
34	49.1	73.6	295	22
36	55.1	82.6	329	30
38	61.3	91.9	365	30
40	68	102	403	30
42	74.5	111.7	442	30
44	82.3	123.5	486	37
46	89.9	134.9	527	37